

Multi-purpose Business Lamp Projector

# NEC ME403U



Bringing exceptional long lamp life performance to the classroom and small meeting room, for classic presentation usage the new generation ME series delivers standard throw projection that's anything but standard. Keeping operational costs to a minimum with no lamp costs to factor in, users enjoy up to 20,000 hours of trouble-free projection and no lamp replacement efforts.

A large 1.6x optical zoom brings impressive integration flexibility making it easier to position the projector in the room, whilst existing ceiling mount locations can be utilised without the need to reposition.

For seamless hand-over between presenters, the projector provides advanced wireless capabilities with an embedded MultiPresenter function, allowing multiple users to connect and share content without having to switch cables.

## Benefits

**Minimized cost of ownership** – due to long lamp life and filter exchange intervals.

**Versatile and mobile** – compact and light-weight with HDMI and integrated 16W speaker.

**Display content that demands attention** – with WUXGA resolution and superb brightness levels and colour ranges, your viewers will enjoy an outstanding visual experience.

**Wide array of flexible application scenarios** – thanks to multi-source conferencing and efficient split-screen operation supported by a wide future-ready range of digital connectivity.

# Specifications

## Product Information

**Product Name**  
NEC ME403U

**Product Group**  
Multi-purpose Business Lamp Projector

**Order Code**  
60005221

## Image

**Projection Technology**  
3LCD Technology

**Native Resolution**  
1920 x 1200  
(WUXGA)

**Aspect Ratio**  
16:10

**Contrast Ratio**  
16000:1

**Brightness**  
3700 Normal / 3000 Lumen Eco; 4200 Centre Lumen; compliant with ISO21118-2012

**Brightness (Boost Mode)**  
4000 Lumen

**Lamp**  
225 W AC (151 W AC Eco Mode)

**Light Source Life [hrs]**  
10000 (20000 Eco Mode)

**Lens**  
F= 1.5–2.08, f= 17.2–27.7 mm

**Keystone correction**  
+/- 30° manual horizontal / +/- 30° automatic / manual vertical

**Projection Angle [°]**  
6.9 - 11.1

**Projection Factor**  
1.2 – 2 : 1

**Projection Distance [m]**  
0.75 – 12.88

**Screen Size (diagonal) [cm] / [inch]**  
Maximum: 762 / 300"; Minimum: 76 / 30"

**Zoom**  
Manual; x1.6

**Focus Adjustment**  
Manual

**Supported Resolutions**  
1920x1200  
(Maximum resolution of analog input)

**Frequency**  
Horizontal: 15–100 kHz (RGB: 24 kHz– 100 kHz); Vertical: 24 – 85 Hz

## Connectivity

**RGB (analog)**  
Input: 1 x Mini D-sub 15-pin, compatible to component (YPbPr)  
Output: 1 x Mini D-sub 15 pin

**Digital**  
Input: 2 x HDMI™ (Deep Color, Lip sync)

**Video**  
Input: 1 x RCA

**Audio**  
Input: 1 x 3.5 mm Stereo Mini Jack; 1 x RCA Stereo  
Output: 1 x 3.5 mm Stereo Mini Jack (variable)

**Control**  
Input: 1 x D-Sub 9 pin (RS-232) (male)

**LAN**  
1 x RJ45; Optional WLAN

**USB**  
1 x Type B; 1x Type A (USB 2.0 high speed) with 1.5 Power Supply

**Video Signals**  
NTSC; PAL; PAL60; SECAM

## Remote Control

**Remote Control**  
Aspect Ratio; Auto Adjust; AV Mute; Digital Zoom; Freeze; ID set; Optional Presentation and Mouse Control

## Electrical

### Power Supply

100-240 V AC; 50 - 60 Hz

### Power Consumption [W]

305 (High Bright) / 220 (Eco) / 1.5 (Network Stand-by) / 0.5 (Stand-by)

## Mechanical

### Dimensions (W x H x D) [mm]

345 x 104.6 x 261 (without lens and feet)

### Weight [kg]

3.5

### Fan Noise [dB (A)]

29 / 37 (Eco / Normal)

### Colour Versions

White

## Environmental Conditions

### Operating Temperature [°C]

5 to 40

### Operating Humidity [%]

20 to 80

### Storage Temperature [°C]

-10 to 50

### Storage Humidity [%]

20 to 80

## Ergonomics

### Safety and Ergonomics

CE; EAC; ErP; RoHS; TUEV Type Approved; WEEE

### Speakers [W]

1 x 16 (mono)

## Additional Features

### Special Characteristics

Auto Eco Mode; Auto Power ON/OFF; Carbon Savings Meter; Colour Management; Content Transmission via Network; Crestron RoomView; DICOM simulation; Direct Power-Off Function; High Altitude Mode; Kensington security slot; Keypad Lock; Lens Cover; Magnify; NaViSet Administrator 2; Off-Timer; Optional WLAN; OSD with 29 languages; Password Security System; Quick On/Off; RS-232 Control; Security Bar; USB Display; USB Viewer for JPEG; Wall Colour Correction

## Green Features

### Energy Efficiency

75 % AV mute function; Auto ECO mode; ECO scheduler; Green one touch ECO and AV mute button; Intelligent power management; Longer light source life; Software scheduling

### Ecological Materials

100% recyclable packaging; Downloadable manuals; ECO packaging

### Ecological Standards

ErP compliant; RoHS compliant; WEEE

## Warranty

### Projectors

3 years pan-European service

### Light Source

6 months, max. 1000 hrs

## Shipping Content

### Shipping Contents

2x AAA Batteries; IR Remote Control (RD-469E); Mini D-SUB Signal Cable (1.8 m); Quick Setup Guide; Security Sticker; Users Manual on CD-ROM; Utility software

## Optional Accessories

### Optional Accessories

Lamp (NP47LP); Universal Ceiling Mounts (Pj01UCM); Wireless LAN module NP05LM2 (Europe), NP05LM4 (Russia)



RoHS



TUEV Type Approved



CE



ErP

This document is © 2025 Sharp Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers.  
All specifications are subject to change without notice. Errors and omissions are excepted. 14.11.2025