

**OVERVIEW**



1. USB-C (USB 10Gbps), with USB PD 65-100W & DP 1.4	5. HDMI
2. Headphone / microphone combo jack (3.5mm)	6. Ethernet (RJ-45)
3. USB-A (USB 5Gbps)	7. USB-A (USB 5Gbps)
4. USB-A (USB 5Gbps)	8. Power connector

## PERFORMANCE

### Processor

#### Processor Family

AMD Ryzen™ 5 / 7 200 Series Processor

#### Processor\*\*

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Processor Graphics	NPU	Overall TOPS
AMD Ryzen™ 5 220	6	12	3.2GHz	4.9GHz	6MB L2 / 16MB L3	AMD Radeon™ 740M	-	-
AMD Ryzen™ 7 250	8	16	3.3GHz	5.1GHz	8MB L2 / 16MB L3	AMD Radeon™ 780M	AMD Ryzen™ AI, up to 16 TOPS	Up to 38 TOPS

### AI (Artificial Intelligence)

#### AI PC Category

AI-Powered Gaming PC<sup>[1]</sup>

#### NPU<sup>[2]</sup>

Integrated AMD Ryzen™ AI, up to 16 TOPS

Notes:

[1] AI-Powered Gaming PCs feature Lenovo® AI Engine+ and NVIDIA® GeForce RTX™ GPUs to handle AI-driven tasks and deliver exceptional gaming performance.

[2] Only for the models with AMD Ryzen™ 7 250 processor.

### Operating System

#### Operating System\*\*

- Windows® 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- No preload operating system

### Graphics

#### Graphics\*\*

Graphics	Type	Memory	Boost Clock	TGP	AI TOPS (Peak)	Key Features
NVIDIA® GeForce RTX™ 5050 Laptop GPU	Discrete	8GB GDDR7	2662 MHz	100W	440 TOPS	DLSS 4, DirectX® 12 Ultimate
NVIDIA® GeForce RTX™ 5060 Laptop GPU	Discrete	8GB GDDR7	2497 MHz	100W	572 TOPS	DLSS 4, DirectX® 12 Ultimate

### Monitor Support

#### Monitor Support

Supports up to 3 independent displays (native display and 2 external monitors via HDMI®, USB-C®)

- HDMI® supports up to 8K@60Hz
- USB-C® supports up to 5K@60Hz

### Chipset

#### Chipset

AMD SoC (System on Chip) platform

### Memory

#### Max Memory<sup>[1]</sup>

Up to 32GB DDR5-5600 offering

#### Memory Slots

Two DDR5 SODIMM slots, dual-channel capable

## Memory Type

DDR5-5600

Notes:

[1] The max memory is based on the test results with current Lenovo® memory offerings.

## Storage

### Max Storage Support<sup>[1][2]</sup>

Up to two drives, 2x M.2 SSD  
 • M.2 2242 SSD up to 1TB each

### Storage Slot<sup>[3]</sup>

Two M.2 slots  
 • One M.2 2280 PCIe® 4.0 x4 slot  
 • One M.2 2280 PCIe® 4.0 x2 slot

### Storage Type

Disk Type	Interface	Offering
M.2 2242 SSD	PCIe® NVMe®, PCIe® 4.0 x4	512GB / 1TB

Notes:

[1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.

[2] The system supports dual SSD via two M.2 slots, but Lenovo® offers only one SSD configuration with a second slot for user self-expansion.

[3] The actual data transfer rate of the following PCIe® interface also depends on the capabilities of the connected PCIe® device. The listed values represent theoretical maximums.

PCIe® 3.0 (x2 / x4): 2 GB/s (16 Gbps) / 4 GB/s (32 Gbps);

PCIe® 4.0 (x2 / x4): 4 GB/s (32 Gbps) / 8 GB/s (64 Gbps);

PCIe® 5.0 (x2 / x4): 8 GB/s (64 Gbps) / 16 GB/s (128 Gbps).

## Removable Storage

### Optical

None

### Card Reader

No card reader

## Multi-Media

### Audio Chip

High Definition (HD) Audio, Realtek® ALC3287 codec

### Speakers

Stereo speakers, 2W x2, optimized with Nahimic Audio

### Microphone

Dual-microphone array

### Camera\*\*

- 5.0MP, with E-shutter, fixed focus
- HD 720p, with E-shutter, fixed focus

## Battery

### Battery

- 60Wh Rechargeable Li-ion Battery, supports Rapid Charge Pro (charge up to 50% in 30min)
- 80Wh Rechargeable Li-ion Battery, supports Rapid Charge Pro (charge up to 50% in 30min)

### Max Battery Life<sup>[1]</sup>

- Models with 60Wh battery:  
 MobileMark® 30@250nits: 4.4 hr  
 Local video (1080p) playback@150nits: 10.4 hr
- Models with 80Wh battery:  
 MobileMark® 25@250nits: 6.5 hr

Local video (1080p) playback@150nits: 12 hr

Notes:

[1] All battery life claims are approximate maximum and based on results using the MobileMark® 2014, MobileMark® 2018, MobileMark® 25, MobileMark® 30, JEITA 2.0, JEITA 3.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary depending on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

**Power Adapter**

**Power Adapter\*\*[1]**

- 170W slim tip (3-pin) AC adapter, 100-240V, 50-60Hz
- 245W slim tip (3-pin) AC adapter, 100-240V, 50-60Hz
- No power adapter

Notes:

[1] AC adapter offerings depend on the country.

**Special Features**

**Special Features**

AI Chip: LA1

**DESIGN**

**Display**

**Display\*\***

Size	Resolution	Touch	Type	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Refresh Rate	Viewing Angle (L/R/U/D)	Key Features
15.6"	FHD (1920x1080)	Non-touch	IPS <sup>[1]</sup>	300nits	Anti-glare	16:9	1000:1	100% sRGB	144Hz	85° / 85° / 85° / 85°	NVIDIA® G-SYNC®, Advanced Optimus support
15.6"	WQHD (2560x1440)	Non-touch	IPS <sup>[2]</sup>	350nits	Anti-glare	16:9	1000:1	100% sRGB	165Hz	85° / 85° / 85° / 85°	3ms response time, Advanced Optimus, NVIDIA® G-SYNC®

**Touchscreen**

Non-touch

**Screen-to-Body Ratio**

88% AAR (active area ratio)

Notes:

[1], [2] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

**Input Device**

**Pen**

No support

**Keyboard**

6-row, multimedia Fn keys, numeric keypad, key travel 1.5mm, cap recess 0.3mm, Copilot key

**Keyboard Backlight\*\***

- 24-Zone RGB backlight
- White backlight

**Touchpad**

Buttonless Mylar® surface multi-touch touchpad, supports Precision TouchPad (PTP), 75 x 120 mm (2.95 x 4.72 inches)

**Mechanical****Dimensions (WxDxH)<sup>[1]</sup>**

359.86 x 258.7 x 21.9-23.9 mm (14.17 x 10.19 x 0.86-0.94 inches)

**Weight<sup>[2]</sup>**

Starting at 2.4 kg (5.29 lbs)

**Case Color**

Luna grey

**Case Material**

PC-ABS (top), PC-ABS (bottom)

**Surface Treatment**

Painting

---

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

**CONNECTIVITY****Network****WLAN + Bluetooth<sup>[1]</sup>**

Wi-Fi® 6, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.3, M.2 card

**WWAN**

No support

**Ethernet**

Gigabit Ethernet, 1x RJ-45

---

Notes:

[1] Wi-Fi® operation (including Wi-Fi® 6, Wi-Fi® 6E, Wi-Fi® 7, etc.) is subject to the regulatory requirements of each country. Bluetooth® may operate at a lower version than hardware design depending on the factors such as operating system, driver, etc.

**Ports<sup>[1]</sup>****Standard Ports<sup>[2]</sup>**

- 3x USB-A (USB 5Gbps / USB 3.2 Gen 1)
- 1x USB-C® (USB 10Gbps / USB 3.2 Gen 2), with USB PD 65-100W and DisplayPort™ 1.4<sup>[3]</sup>
- 1x HDMI® 2.1, up to 8K/60Hz
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Ethernet (RJ-45)
- 1x Slim tip Power connector

---

Notes:

[1], [2] The transfer speed of the ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

[3] Supports Lenovo® protocol for 140W charging but requires a unique Lenovo® adapter for operation.

**Docking****Docking**

Various docking solutions supported via or USB-C®.  
For more compatible docking solutions, please visit

[Docking for LOQ™ 15AHP10](#)

## SECURITY & PRIVACY

### Security

#### Security Chip

Firmware TPM 2.0 integrated in SoC

#### Fingerprint Reader

No fingerprint reader

#### BIOS Security

- Administrator password
- Hard disk password
- Master hard disk password
- Power-on password
- User hard disk password
- User password
- Self-healing BIOS
- More BIOS security features, please visit [BIOS Simulator](#)

#### Other Security

E-shutter

## SERVICE

### Warranty

#### Base Warranty\*\*

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 2-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) courier or carry-in service

## ACCESSORIES

### Bundled Accessories

#### Bundled Accessories

- Lenovo® LOQ™ M100 RGB Mouse (USB connector)
- None

## OPERATING REQUIREMENTS

### Operating Environment

#### Temperature<sup>[1]</sup>

At altitudes up to 2438 m (8,000 ft)

- Operating: 5°C to 35°C (41°F to 95°F)

- Storage: 5°C to 43°C (41°F to 109°F)

#### Relative Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)

#### Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

## CERTIFICATIONS

## Green Certifications<sup>[1]</sup>

### Green Certifications

- ErP Lot 6/26
- RoHS compliant

---

#### Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <https://compliance.lenovo.com>.

## Other Certifications

### Other Certifications

TÜV Rheinland® Low Blue Light (Software Solution)

- Feature with \*\* means that only one option listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS", WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.



AMD




AMD



AMD



AMD



AMD



AMD