

i-tec USB4 Metal Docking station Dual 4K HDMI DP + Power Delivery 80 W

i-tec USB4 Metal Docking station Dual 4K HDMI DP + Power Delivery 80 W



PRODUCT DESCRIPTION

The latest and fastest generation of USB technology is finally here. The most powerful USB docking station, super-fast data transfer and support for up to 8K* resolution.

Crystal clear image quality, fast internet and the ability to transfer data at speeds of over 1GB per second even when using multiple USB ports simultaneously. You can also, of course, connect your headphones or audio and charge your laptop (80W), all using one single cable.

Thanks to the integrated DP 1.4 protocol, you can connect this dock to a monitor with a resolution of up to 8K $(7680 \times 4320)^*$ with a refresh rate of 30 Hz, which is equivalent to the resolution of four monitors, each at 4K resolution. This makes it the ideal solution for graphic designers, analysts, developers, film editors, or high-definition video enthusiasts and lovers.

Since USB4 technology is backwards compatible, you can connect this dock not only to laptops and tablets with USB4, but also ThunderboltTM 3/4 and USB-C (must support video transfer). This makes the dock an ideal and flexible solution for businesses and users who run laptops and tablets with different ports.

* 8K resolution must be supported by the connected laptop or tablet.

PRODUCT FEATURES

- 1x USB4 port for connection to a compatible device
- Docking station technology: USB4
- Power Delivery: 80 W (power adapter not included)
- Video Ports:



- 1x HDMI
- 1x DisplayPort
- Resolution:
- USB4/Thunderbolt™ 4 Host device with DisplayPort 1.4 support:
 - 1 monitor 1x HDMI or DP → up to 8K/30Hz*
 - 1 monitor 1x HDMI or DP → up to 4K/144Hz or 1440p/240Hz or 1080p/360Hz
 - \circ 2 monitors HDMI + DP → up to 2x 4K/60Hz
 - \circ 2 monitor HDMI + DP → up to 2x 1440p/144Hz

USB-C/Thunderbolt™ 3 Host device with DisplayPort 1.4 with DSC support:

- 1 monitor 1x HDMI or DP → up to 5K/60Hz (bylo zde 5K)
- \circ 1 monitor 1x HDMI or DP \rightarrow up to 4K/144Hz or 1440p/240Hz or 1080p/360Hz
- \circ 2 monitors HDMI + DP → up to 2x 4K/60Hz
- \circ 2 monitors HDMI + DP \rightarrow up to 2x 1440p/144Hz

• USB-C/Thunderbolt™ 3 Host device with DisplayPort 1.4 support:

- ∘ 1 monitor 1x HDMI or DP \rightarrow up to 4K/60Hz
- \circ 2 monitors HDMI + DP \rightarrow up to 2x 1440p/60Hz or 2x 1440p/144Hz

USB-C/Thunderbolt™ 3 Host device with DisplayPort 1.2 support:

- \circ 1 monitor 1x HDMI or DP → up to 4K/30Hz
- ∘ 1 monitor 1x HDMI or DP \rightarrow up to 1080p/120Hz
- \circ 2 monitors HDMI + DP \rightarrow up to 2x 1080p/60Hz
- 1x USB-C 3.2 Gen. 2 port (data only)
- 3x USB-A 3.2 port Gen. 2 with fast charging support (BC 1.2)
- 3x USB 2.0
- 1x Ethernet GLAN RJ-45 port (ASIX AX88179)
- 1x SD / microSD slot
- 1x 3.5mm Audio combo jack
- MAC Address cloning: Yes (using <u>i-tec Docker Pro</u> software)
- WOL: S1, S2, S3
- LED indication
- USB4 cable (80 cm)
- OS: Windows 10/11, macOS, Linux and iPadOS with latest updates
- Product dimensions: 69 x 128 x 48 mm
- Product weight: 314 g
- Package dimensions: 173 x 150 x 56 mm
- Package weight: 526 g

Hardware Requirements:

• Device with a free USB-C, USB4 or Thunderbolt™ 3/4 port

Power Delivery Requirements:

• Device with a free USB-C, USB4 or Thunderbolt™ 3/4 port with Power Delivery support

Video Output Requirements:

Device with a free USB-C or USB4 port with DisplayPort Alternate Mode support or a Thunderbolt™ 3/4 port

Operating System:

• Windows 10 / 11, macOS and Linux with latest updates

^{* 8}K resolution must be supported by the connected laptop or tablet.



iPadOS, Android do not support multi-screen video transfer technology, nor the extended screen option. This means that when connected to an external monitor, only a mirrored screen will be displayed. (Not valid for androids with DEX and Easy Projection add-ons) Power supply is not included. The docking station can be used with the power supply supplied with the laptop or a power supply can be purchased separately, e.g. 100W: P/N CHARGER-C112W/UK.

SPECIFICATION

Part Number	Product Description & EAN
USB4DUAL4KDOCKPD	i-tec USB4 Metal Docking station Dual 4K HDMI DP + Power Delivery 80 W
	EAN: 8595611705434
Hardware	
Bus type	USB4, Thunderbolt-3, Thunderbolt-4, USB-C
Ports/Connectors	
System Requirements	
Operating system	Windows 10/11 macOS X Linux
Other features	
Colour	black
Housing Material	Aluminium
Product Dimensions	69 x 128 x 48 mm
Product Weight	314 g
Package Weight	526 g
Packaging Dimensions (LxWxH)	173 x 150 x 56 mm
Support	
Warranty period	2 years
Technical support	lifetime
Package contents	
Product	
USB4 connection cable (80 cm)	
Manual	

For further information regarding setup or for answers to FAQ's, please visit our website <u>i-tec.pro</u>. Specifications are subject to change without notice.

Updated 14.4.2023