

OVERVIEW



|                                  |                                                          |
|----------------------------------|----------------------------------------------------------|
| 1. USB-A (USB 5Gbps)             | 5. Thunderbolt 4 / USB-C (USB 20Gbps), PD 3.1 & DP 1.4 * |
| 2. Ethernet (RJ-45)              | 6. Thunderbolt 4                                         |
| 3. Kensington Nano Security Slot | 7. USB-A (USB 10Gbps), Always On                         |
| 4. HDMI                          | 8. Headphone / microphone combo jack (3.5mm)             |

Notes:

- Items with \* are only available on selected models
- Port 5 is Thunderbolt 4 (models with Lunar Lake) or USB-C (models with Raptor Lake, Meteor Lake and Arrow Lake)

PERFORMANCE

Processor

Processor Family

- Intel® H Series Core Ultra 5 / 9 Processor (Series 1) - Meteor Lake (MTL)
- Intel® U Series Core 3 Processor (Series 1) - Raptor Lake (RPL)
- Intel® U or H Series Core 5 / 7 Processor (Series 2) - Raptor Lake (RPL)
- Intel® U or H Series Core Ultra 5 / 7 Processor (Series 2) - Arrow Lake (ARL)
- Intel® V Series Core Ultra 5 / 7 Processor (Series 2) - Lunar Lake (LNL)

Processor\*\*

| Processor Name                         | Cores                                  | Threads | Base Frequency                                   | Max Frequency                                    | Cache                   | Processor Graphics                                 | NPU                            | Intel® vPro® Eligibility | Overall TOPS   |
|----------------------------------------|----------------------------------------|---------|--------------------------------------------------|--------------------------------------------------|-------------------------|----------------------------------------------------|--------------------------------|--------------------------|----------------|
| Core Ultra 5 225H (ARL)                | 14 (4 P-core + 8 E-core + 2 LP E-core) | 14      | P-core 1.7GHz / E-core 1.3GHz / LP E-core 700MHz | P-core 4.9GHz / E-core 4.3GHz / LP E-core 2.5GHz | 18MB Intel® Smart Cache | Intel® Arc™ 130T GPU, up to 63 TOPS <sup>[1]</sup> | Intel® AI Boost, up to 13 TOPS | -                        | Up to 83 TOPS  |
| Core Ultra 5 225U (ARL)                | 12 (2 P-core + 8 E-core + 2 LP E-core) | 14      | P-core 1.5GHz / E-core 1.3GHz / LP E-core 700MHz | P-core 4.8GHz / E-core 3.8GHz / LP E-core 2.4GHz | 12MB Intel® Smart Cache | Intel® Graphics, up to 8 TOPS                      | Intel® AI Boost, up to 12 TOPS | -                        | Up to 24 TOPS  |
| Core Ultra 5 226V (LNL)                | 8 (4 P-core + 4 LP E-core)             | 8       | P-core 2.1GHz / LP E-core 2.1GHz                 | P-core 4.5GHz / LP E-core 3.5GHz                 | 8MB Intel® Smart Cache  | Intel® Arc™ Graphics 130V, up to 53 TOPS           | Intel® AI Boost, up to 40 TOPS | -                        | Up to 97 TOPS  |
| Core Ultra 5 228V (LNL)                | 8 (4 P-core + 4 LP E-core)             | 8       | P-core 2.1GHz / LP E-core 2.1GHz                 | P-core 4.5GHz / LP E-core 3.5GHz                 | 8MB Intel® Smart Cache  | Intel® Arc™ Graphics 130V, up to 53 TOPS           | Intel® AI Boost, up to 40 TOPS | -                        | Up to 97 TOPS  |
| Core Ultra 5 236V (LNL) <sup>[2]</sup> | 8 (4 P-core + 4 LP E-core)             | 8       | P-core 2.1GHz / LP E-core 2.1GHz                 | P-core 4.7GHz / LP E-core 3.5GHz                 | 8MB Intel® Smart Cache  | Intel® Arc™ Graphics 130V, up to 53 TOPS           | Intel® AI Boost, up to 40 TOPS | Intel® vPro® Enterprise  | Up to 97 TOPS  |
| Core Ultra 5 238V (LNL)                | 8 (4 P-core + 4 LP E-core)             | 8       | P-core 2.1GHz / LP E-core 2.1GHz                 | P-core 4.7GHz / LP E-core 3.5GHz                 | 8MB Intel® Smart Cache  | Intel® Arc™ Graphics 130V, up to 53 TOPS           | Intel® AI Boost, up to 40 TOPS | Intel® vPro® Enterprise  | Up to 97 TOPS  |
| Core Ultra 5 235U (ARL)                | 12 (2 P-core + 8 E-core + 2 LP E-core) | 14      | P-core 2.0GHz / E-core 1.6GHz / LP E-core 700MHz | P-core 4.9GHz / E-core 4.1GHz / LP E-core 2.4GHz | 12MB Intel® Smart Cache | Intel® Graphics, up to 8 TOPS                      | Intel® AI Boost, up to 12 TOPS | Intel® vPro® Enterprise  | Up to 24 TOPS  |
| Core Ultra 7 256V (LNL)                | 8 (4 P-core + 4 LP E-core)             | 8       | P-core 2.2GHz / LP E-core 2.2GHz                 | P-core 4.8GHz / LP E-core 3.7GHz                 | 12MB Intel® Smart Cache | Intel® Arc™ Graphics 140V, up to 64 TOPS           | Intel® AI Boost, up to 47 TOPS | -                        | Up to 115 TOPS |
| Core Ultra 7 258V (LNL)                | 8 (4 P-core + 4 LP E-core)             | 8       | P-core 2.2GHz / LP E-core 2.2GHz                 | P-core 4.8GHz / LP E-core 3.7GHz                 | 12MB Intel® Smart Cache | Intel® Arc™ Graphics 140V, up to 64 TOPS           | Intel® AI Boost, up to 47 TOPS | -                        | Up to 115 TOPS |
| Core Ultra 7 265U (ARL)                | 12 (2 P-core + 8 E-core + 2 LP E-core) | 14      | P-core 2.1GHz / E-core 1.7GHz / LP E-core 700MHz | P-core 5.3GHz / E-core 4.2GHz / LP E-core 2.4GHz | 12MB Intel® Smart Cache | Intel® Graphics, up to 8 TOPS                      | Intel® AI Boost, up to 12 TOPS | Intel® vPro® Enterprise  | Up to 24 TOPS  |
| Core Ultra 7 255H                      | 16 (6 P-core + 8                       | 16      | P-core 2.0GHz / E-core 1.5GHz                    | P-core 5.1GHz / E-core                           | 24MB Intel®             | Intel® Arc™ 140T GPU, up                           | Intel® AI Boost,               | -                        | Up to 96       |

|                                  |                                        |    |                                                  |                                                  |                         |                                                    |                                |                         |                |
|----------------------------------|----------------------------------------|----|--------------------------------------------------|--------------------------------------------------|-------------------------|----------------------------------------------------|--------------------------------|-------------------------|----------------|
| (ARL)                            | E-core + 2 LP E-core)                  |    | / LP E-core 700MHz                               | 4.4GHz / LP E-core 2.5GHz                        | Smart Cache             | to 74 TOPS <sup>[3]</sup>                          | up to 13 TOPS                  |                         | TOPS           |
| Core Ultra 7 266V (LNL)          | 8 (4 P-core + 4 LP E-core)             | 8  | P-core 2.2GHz / LP E-core 2.2GHz                 | P-core 5.0GHz / LP E-core 3.7GHz                 | 12MB Intel® Smart Cache | Intel® Arc™ Graphics 140V, up to 66 TOPS           | Intel® AI Boost, up to 48 TOPS | Intel® vPro® Enterprise | Up to 118 TOPS |
| Core Ultra 7 268V (LNL)          | 8 (4 P-core + 4 LP E-core)             | 8  | P-core 2.2GHz / LP E-core 2.2GHz                 | P-core 5.0GHz / LP E-core 3.7GHz                 | 12MB Intel® Smart Cache | Intel® Arc™ Graphics 140V, up to 66 TOPS           | Intel® AI Boost, up to 48 TOPS | Intel® vPro® Enterprise | Up to 118 TOPS |
| Core Ultra 9 185H                | 16 (6 P-core + 8 E-core + 2 LP E-core) | 22 | P-core 2.3GHz / E-core 1.8GHz / LP E-core 1.0GHz | P-core 5.1GHz / E-core 3.8GHz / LP E-core 2.5GHz | 24MB Intel® Smart Cache | Intel® Arc™ Graphics, up to 19 TOPS <sup>[4]</sup> | Intel® AI Boost, up to 11 TOPS | -                       | Up to 35 TOPS  |
| Core Ultra 5 135H (MTL)          | 14 (4 P-core + 8 E-core + 2 LP E-core) | 18 | P-core 1.7GHz / E-core 1.2GHz / LP E-core 700MHz | P-core 4.6GHz / E-core 3.6GHz / LP E-core 2.5GHz | 18MB Intel® Smart Cache | Intel® Arc™ Graphics, up to 18 TOPS <sup>[5]</sup> | Intel® AI Boost, up to 11 TOPS | -                       | Up to 33 TOPS  |
| Core 3 100U (RPL)                | 6 (2 P-core + 4 E-core)                | 8  | P-core 1.2GHz / E-core 900MHz                    | P-core 4.7GHz / E-core 3.3GHz                    | 10MB Intel® Smart Cache | Intel® Graphics                                    | -                              | -                       | -              |
| Core 5 210H (RPL)                | 8 (4 P-core + 4 E-core)                | 12 | P-core 2.2GHz / E-core 1.6GHz                    | P-core 4.8GHz / E-core 3.6GHz                    | 12MB Intel® Smart Cache | Intel® Graphics                                    | -                              | -                       | -              |
| Core 5 220U (RPL)                | 10 (2 P-core + 8 E-core)               | 12 | P-core 1.4GHz / E-core 900MHz                    | P-core 5.0GHz / E-core 3.8GHz                    | 12MB Intel® Smart Cache | Intel® Graphics                                    | -                              | -                       | -              |
| Core 7 240H (RPL)                | 10 (6 P-core + 4 E-core)               | 16 | P-core 2.5GHz / E-core 1.8GHz                    | P-core 5.2GHz / E-core 4.0GHz                    | 24MB Intel® Smart Cache | Intel® Graphics                                    | -                              | -                       | -              |
| Core 7 250U (RPL) <sup>[6]</sup> | 10 (2 P-core + 8 E-core)               | 12 | P-core 1.8GHz / E-core 1.2GHz                    | P-core 5.4GHz / E-core 4.0GHz                    | 12MB Intel® Smart Cache | Intel® Graphics                                    | -                              | -                       | -              |

Notes:

[1], [3], [4], [5] Intel® Arc™ Graphics only available on select H-series Intel® Core™ Ultra processor powered systems with at least 16GB of system memory in a dual-channel configurations, otherwise it will function as Intel® Graphics.

[2] Intel® Core™ Ultra 5 236V is for special bid only.

[6] Intel® Core™ 7 250U is for special bid only.

AI (Artificial Intelligence)

AI PC Category\*\*

- AI PC (Meteor Lake and Arrow Lake)<sup>[1]</sup>
- Copilot+ PC (Lunar Lake)<sup>[2]</sup>

NPU

Integrated Intel® AI Boost, up to 48 TOPS

Notes:

[1] AI PCs have a NPU capable of 10+ TOPs to run the Copilot assistant by pressing the optional Microsoft® Copilot key or using Win + C.

[2] Copilot+ PCs have at least 16GB RAM, 256GB storage, and a NPU that runs 40+ TOPs to run the latest AI tools build-in latest Windows® 11 to accelerate productivity and creativity.

## Operating System

### Operating System\*\*

- Windows® 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- Ubuntu Linux<sup>[1]</sup>
- No preload operating system

Notes:

[1] Ubuntu Linux is available for MT 21TF/21TG only.  
Some features may not be supported on the system with Linux preload, including but not limited to Intel® RST RAID, MIPI computer vision camera, WWAN, Human Presence Detection, etc.

## Graphics

### Graphics\*\*

| Graphics                            | Type       | Memory | Key Features  |
|-------------------------------------|------------|--------|---------------|
| Intel® Graphics                     | Integrated | Shared | DirectX® 12.2 |
| Intel® Arc™ 130T GPU <sup>[1]</sup> | Integrated | Shared | DirectX® 12.2 |
| Intel® Arc™ 140T GPU <sup>[2]</sup> | Integrated | Shared | DirectX® 12.2 |
| Intel® Arc™ Graphics <sup>[3]</sup> | Integrated | Shared | DirectX® 12.2 |
| Intel® Arc™ Graphics 130V           | Integrated | Shared | DirectX® 12.2 |
| Intel® Arc™ Graphics 140V           | Integrated | Shared | DirectX® 12.2 |

Notes:

[1], [2] Intel® Arc™ graphics only available on select H-series Intel® Core™ Ultra processor powered systems with at least 16GB of system memory in a dual-channel configurations, otherwise it will function as Intel® Graphics.  
[3] Intel® Arc™ Graphics only available on select H-series Intel® Core™ Ultra processor powered systems with at least 16GB of system memory in a dual-channel configurations, otherwise it will function as Intel® Graphics.

## Monitor Support

### Monitor Support<sup>[1]</sup>

- Raptor Lake, Meteor Lake and Arrow Laker: supports up to 4 independent displays (native display and 3 external monitors via HDMI®, USB-C® and Thunderbolt™)
  - HDMI® supports up to 4096x2160@60Hz
  - USB-C® supports up to 5120x2880@60Hz
  - Thunderbolt™ supports up to 7680x4320@60Hz<sup>[2]</sup>
- Lunar Lake: supports up to 3 independent displays (native display and 2 external monitors via HDMI® and Thunderbolt™)
  - HDMI® supports up to 4096x2160@60Hz
  - Thunderbolt™ supports up to 7680x4320@60Hz<sup>[3]</sup>

Notes:

[1] Refresh rates >60hz also supported, however max resolution will be limited.  
[2], [3] 8K resolution support needs 2 display pipes. That is, simultaneous display number will “-1” when 8K resolution displayed.

## Chipset

### Chipset

Intel® SoC (System on Chip) platform

## Memory

### Max Memory

- Lunar Lake: 16GB soldered memory, not upgradable
- Lunar Lake: 32GB soldered memory, not upgradable

- Raptor Lake with U Series processors: up to 64GB DDR5-5200<sup>[1]</sup>
- Raptor Lake with H Series processors, Meteor Lake and Arrow Lake: up to 64GB DDR5-5600<sup>[2]</sup>

Memory Slots

- Lunar Lake: memory soldered to systemboard, no slots, dual-channel
- Raptor Lake, Meteor Lake and Arrow Lake: two DDR5 SODIMM slots, dual-channel capable

Memory Type

- Lunar Lake: LPDDR5X-8533, MoP (Memory on Package) memory
- Raptor Lake with U Series processors: DDR5-5200<sup>[3]</sup>
- Raptor Lake with H Series processors, Meteor Lake and Arrow Lake: DDR5-5600

Notes:

- [1], [2] The 64GB memory is for special bid only.
- [3] Installed memory is actually DDR5-5600 but runs as DDR5-5200 due to platform limitation.

Storage

Max Storage Support

- Raptor Lake, Meteor Lake and Arrow Lake:  
up to two drives, 2x M.2 SSD
  - M.2 2242 SSD up to 1TB
  - M.2 2280 SSD up to 1TB<sup>[1]</sup>
- Lunar Lake:  
one drive, up to 1TB M.2 2280 SSD

Storage Slot<sup>[2]</sup>

- Lunar Lake: one M.2 2280 PCIe® 4.0 x4 slot
- Raptor Lake, Meteor Lake and Arrow Lake: two M.2 slots
  - One M.2 2242 PCIe® 4.0 x4 slot
  - One M.2 2280 PCIe® 4.0 x4 slot

Storage Type

| Disk Type    | Interface                 | Offering            | Security |
|--------------|---------------------------|---------------------|----------|
| M.2 2242 SSD | PCIe® NVMe®, PCIe® 4.0 x4 | 256GB / 512GB / 1TB | Opal 2.0 |

Notes:

- [1] The system supports dual SSD via two M.2 slots, but Lenovo® offers only one SSD configuration with a second slot for user self-expansion.
- [2] The actual data transfer rate of the following PCIe® interface also depends on the capabilities of the connected PCIe® device. The listed values represent theoretical maximums.
- PCIe® 3.0 (x2 / x4): 2 GB/s (16 Gbps) / 4 GB/s (32 Gbps);
- PCIe® 4.0 (x2 / x4): 4 GB/s (32 Gbps) / 8 GB/s (64 Gbps);
- PCIe® 5.0 (x2 / x4): 8 GB/s (64 Gbps) / 16 GB/s (128 Gbps).

Removable Storage

Card Reader

No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Senary SN6147 codec

Speakers

Stereo speakers, 2W x2, Dolby Atmos®, audio by HARMAN

Microphone

Dual-microphone array, 360° far-field, smart noise-cancelling

Camera\*\*

- 5.0MP, with privacy shutter, fixed focus, temporal noise reduction
- FHD 1080p + IR hybrid, with privacy shutter, fixed focus, temporal noise reduction
- HD 720p, with privacy shutter, fixed focus

Battery

Battery\*\*

- 48Wh Rechargeable Li-ion Battery, supports Rapid Charge Pro (charge up to 50% in 30min)<sup>[1]</sup>
- 64Wh Rechargeable Li-ion Battery, supports Rapid Charge (charge up to 80% in 1hr)

Battery Life<sup>[2]</sup>

Configuration 1 (max battery life)  
MobileMark® 30: up to 11.08 hr with 699 performance score @250nits  
JEITA-BAT 3.0 (Video/Idle): up to 11.36 hr / 24.08 hr @200nits  
Local video playback: up to 20.4 hr @150nits

Configuration 2  
MobileMark® 30: up to 8.81 hr with 681 performance score @250nits  
JEITA-BAT 3.0 (Video/Idle): up to 10.3 hr / 18.9 hr @200nits  
Local video playback: up to 19.5 hr @150nits

Configuration 3  
MobileMark® 30: up to 8.6 hr with 868 performance score @250nits  
JEITA-BAT 3.0 (Video/Idle): up to 7.43 hr / 17.2 hr @200nits  
Local video playback: up to 15.11 hr @150nits

Notes:

[1] Rapid charge is only guaranteed when the computer is turned off or in standby mode or in hibernation mode. When the computer is powered on, the Charge Time will vary depending on system power consumption and AC adapter power.

[2] Configuration 1: WUXGA (non-touch), Intel® Core™ Ultra 5 225U, 16GB DDR5, Win 11, 64Wh battery, best power efficiency power mode

Configuration 2: WUXGA (non-touch), Intel® Core™ 3 100U, 8GB DDR5, Win 11, 64Wh battery, best power efficiency power mode

Configuration 3: WQXGA (non-touch), Intel® Core™ Ultra 7 255H, 64GB DDR5, Win 11, 64Wh battery, best power efficiency power mode

All battery life claims are approximate maximum and based on results using [MobileMark® 30](#), JEITA 3.0, continuous 1080p local video playback (using default Media Player in Fullscreen mode with 150nits brightness and default volume level), or Google Power Load Test (PLT) battery-life benchmark tests.

Actual battery life will vary and depends on many factors such as product configuration, software, wireless functionality, power management settings, and screen brightness.

The maximum capacity of the battery will decrease with time, ambient temperature and use.

Refer to [Microsoft® link](#) for more information about the Windows® Performance power slider.

Power Adapter

Power Adapter\*\*<sup>[1]</sup>

- 65W USB-C® (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® slim (2-pin, wall-mount) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- No power adapter

Notes:

[1] AC adapter offerings depend on the country.

DESIGN

Display

Display\*\*

| Size | Resolution        | Touch     | Type               | Brightness | Surface    | Aspect Ratio | Contrast Ratio | Color Gamut | Refresh Rate | Viewing Angle (L/R/U/D) | Key Features                             |
|------|-------------------|-----------|--------------------|------------|------------|--------------|----------------|-------------|--------------|-------------------------|------------------------------------------|
| 16"  | WUXGA (1920x1200) | Non-touch | IPS <sup>[1]</sup> | 300nits    | Anti-glare | 16:10        | 800:1          | 45% NTSC    | 60Hz         | 85° / 85° / 85° / 85°   | TÜV Rheinland® Low Blue Light (Software) |

|     |                      |             |                    |         |            |       |        |           |           |                       |                                          |
|-----|----------------------|-------------|--------------------|---------|------------|-------|--------|-----------|-----------|-----------------------|------------------------------------------|
| 16" | WUXGA<br>(1920x1200) | Multi-touch | IPS <sup>[2]</sup> | 300nits | Anti-glare | 16:10 | 800:1  | 45% NTSC  | 60Hz      | 89° / 89° / 89° / 89° | TÜV Rheinland® Low Blue Light (Software) |
| 16" | WQXGA<br>(2560x1600) | Non-touch   | IPS <sup>[3]</sup> | 400nits | Anti-glare | 16:10 | 1200:1 | 100% sRGB | 120Hz VRR | 89° / 89° / 89° / 89° | Eyesafe® Certified 2.0                   |

Touchscreen

- In-cell multi-touch, supports 10-point touch
- Non-touch

Screen-to-Body Ratio

90.7%

Notes:

[1], [2], [3] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

Input Device

Pen

No support

Keyboard

6-row, spill-resistant, multimedia Fn keys, numeric keypad, key travel 1.5mm / 1.35mm (Fn row & G/H/B), Copilot key

Keyboard Backlight

- LED backlight
- Non-backlight

UltraNav™

TrackPoint® pointing device, double-tap to open the TrackPoint® Quick Menu  
Mylar® surface multi-touch 3-button Trackpad, 67 x 115 mm (2.64 x 4.53 inches)

Mechanical

Dimensions (WxDxH)<sup>[1]</sup>

| Models                                             | Dimensions                                                                                                               |
|----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| Models with aluminium (top) and aluminium (bottom) | 356 x 249 x 10.1/17.05 (front/rear), 21.15 (maximum) mm;<br>14.01 x 9.80 x 0.40/0.67 (front/rear), 0.83 (maximum) inches |
| Models with aluminium (top) and PC-ABS (bottom)    | 356 x 249 x 10.1/17.05 (front/rear), 21.95 (maximum) mm;<br>14.01 x 9.8 x 0.40/0.67 (front/rear), 0.86 (maximum) inches  |

Weight<sup>[2]</sup>

| Models                                  | Weight                         |
|-----------------------------------------|--------------------------------|
| Lunar Lake                              | Starting at 1.61 kg (3.55 lbs) |
| Raptor Lake, Meteor Lake and Arrow Lake | Starting at 1.63 kg (3.59 lbs) |

Case Color

Black

Case Material\*\*

- Aluminium (top), PC-ABS (bottom)
- Aluminium (top), aluminium (bottom)

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

## Network

### WLAN + Bluetooth®\*\*<sup>[1]</sup>

- Wi-Fi® 6, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.3, M.2 card
- Realtek® Wi-Fi® 6 RTL8852BE, 802.11ax Dual Band 2x2 Wi-Fi® + Bluetooth® 5.3, M.2 card
- Intel® Wi-Fi® 6 AX203, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.2, M.2 card
- Wi-Fi® 6E, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.3, M.2 card
- Intel® Wi-Fi® 6E AX211, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.3, Intel® vPro® technology support, M.2 card<sup>[2]</sup>
- Intel® Wi-Fi® 6E AX211, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.3, M.2 card
- Wi-Fi® 7, 802.11be 2x2 Wi-Fi® + Bluetooth® 5.4, M.2 card
- MediaTek Wi-Fi® 7 MT7925, 802.11be 2x2 Wi-Fi® + Bluetooth® 5.4, M.2 card
- Intel® Wi-Fi® 7 BE200, 802.11be 2x2 Wi-Fi® + Bluetooth® 5.4, Intel® vPro® technology support, M.2 card<sup>[3]</sup>
- Intel® Wi-Fi® 7 BE200, 802.11be 2x2 Wi-Fi® + Bluetooth® 5.4, M.2 card

### WWAN

No support

### Ethernet\*\*

- Gigabit Ethernet, Intel® Ethernet Connection I219-LM (vPro® models), 1x RJ-45, supports Wake-on-LAN
- Gigabit Ethernet, Intel® Ethernet Connection I219-V (non-vPro® models), 1x RJ-45, supports Wake-on-LAN

### NFC

No support

Notes:

[1] Wi-Fi® operation (including Wi-Fi® 6, Wi-Fi® 6E, Wi-Fi® 7, etc.) is subject to the regulatory requirements of each country. Bluetooth® may operate at a lower version than hardware design depending on the factors such as operating system, driver, etc.

[2], [3] Intel® vPro® platform requires the hardware and software necessary to deliver the manageability use cases, security features, system performance, and stability that define the platform. For detailed vPro® support information, please refer to the System Management section.

## Ports<sup>[1]</sup>

### Standard Ports

- 1x USB-A (USB 5Gbps / USB 3.2 Gen 1)
- 1x USB-A (USB 10Gbps / USB 3.2 Gen 2), Always On
- 1x USB-C® (Thunderbolt™ 4 / USB4® 40Gbps), with USB PD 15-65W and DisplayPort™ 2.1
- 1x HDMI® 2.1, up to 4K/60Hz
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Ethernet (RJ-45)

### Optional Ports

- Lunar Lake: 1x USB-C® (Thunderbolt™ 4 / USB4® 40Gbps), with USB PD 15-65W and DisplayPort™ 2.1
- Raptor Lake, Meteor Lake and Arrow Lake: 1x USB-C® (USB 20Gbps / USB 3.2 Gen 2x2), with USB PD 15-65W and DisplayPort™ 1.4

Notes:

[1] The transfer speed of the ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

## Docking

### Docking

Various docking solutions supported via Thunderbolt™ / USB-C®.

For more compatible docking solutions, please visit [Docking for ThinkPad® E16 Gen 3 \(Intel®\)](#)

## SECURITY & PRIVACY

## Security

### ThinkShield

ThinkShield is a comprehensive security solution that encompasses hardware, software, and supply chain components. For more details, visit [here](#)

**Security Chip**

Discrete TPM 2.0, TCG certified, FIPS 140-3 certified

**Physical Locks**

Kensington® Nano Security Slot™, 2.5 x 6 mm

**Smart Card Reader**

No smart card reader

**Fingerprint Reader**

- Touch style fingerprint reader integrated in power button, match-on-chip
- No fingerprint reader

**BIOS Security**

- Certificate-based BIOS authentication
- FIDO (Fast Identity Online) authentication
- NVMe® password
- Power-on password
- Supervisor password
- System management password
- Self-healing BIOS
- More BIOS security features (Arrow Lake), please visit [BIOS Simulator](#)<sup>[1]</sup>
- More BIOS security features (Raptor Lake), please visit [BIOS Simulator](#)<sup>[2]</sup>

**Other Security**

- Camera privacy shutter
- (Optional) IR camera for Windows® Hello (facial recognition)

---

Notes:

[1], [2] The BIOS simulator is just for reference. Default settings and some options may vary depending on the hardware, operating system and BIOS version.

## MANAGEABILITY

### System Management

**System Management**<sup>[1]</sup>

- Intel® vPro® Enterprise<sup>[2]</sup>
- Non-vPro®

---

Notes:

[1] Intel® vPro® platform require an eligible Intel® processor, a supported operating system, Intel® LAN and/or WLAN silicon, firmware enhancements, and other hardware and software necessary to deliver the manageability use cases, security features, system performance, and stability that define the platform. See [Intel® vPro® Platform](#) for details.

[2] Intel® vPro® offers a superset of DASH's defined capabilities.

## SERVICE

### Warranty

**Base Warranty**<sup>\*\*</sup>

- 1-year mail-in service
- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 1-year limited onsite service
- No base warranty

## ACCESSORIES

### Bundled Accessories

**Bundled Accessories**<sup>[1]</sup>

- Lenovo® 15.6" laptop casual toplayer, polyester

- None

Notes:

[1] For more compatible accessory solutions, please visit [Accessories for ThinkPad® E16 Gen 3 \(Intel®\)](#).

## OPERATING REQUIREMENTS

### Operating Environment

#### Temperature<sup>[1]</sup>

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage and transportation in original shipping package: -20°C (-4°F ) to 60°C (140°F)
- Storage without package: 5°C (41°F) to 43°C (109°F)

#### Relative Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

#### Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

## ENVIRONMENTAL

### Sustainability

#### Material<sup>[1]</sup>

50% recycled aluminium on top cover  
50% PCC recycled plastic used in display panel frame  
50% recycled aluminium on metal bottom cover  
50% PCC recycled plastic used in PC-ABS bottom cover  
90% PCC recycled plastic used in battery pack enclosure  
85% PCC recycled plastic used in key caps (backlight)  
70% PCC recycled plastic used in key caps (non-backlight)  
90% PCC recycled plastic used in speaker enclosure  
90% PCC recycled plastic used in standard 65W adapter  
FSC certified plastic-free packaging: screen film, accessory box, carton  
Bamboo + sugarcane fiber standard / retail packaging

Notes:

[1] PCC: Post Consumer Content, recycled materials from customers.

## CERTIFICATIONS

### Green Certifications<sup>[1]</sup>

#### Green Certifications<sup>[2]</sup>

- ENERGY STAR® 9.0
- EPEAT™ Gold Registered<sup>[3]</sup>
- ErP Lot 6/26
- RoHS compliant
- TCO Certified, generation 10

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <https://compliance.lenovo.com>.

[2] EPEAT™ registration and ENERGY STAR® certification are optional and only available on the models with preloaded OS. Please visit [epeat.net](https://epeat.net) and [energystar.gov](https://energystar.gov) for more information.

[3] EPEAT™ is registered where applicable, please visit [epeat.net](https://epeat.net) for registration status by country.

## Other Certifications

### Mil-Spec Test

MIL-STD-810H military test passed

### Other Certifications

- (Optional) Eyesafe® Certified 2.0
- (Optional) TÜV Rheinland® Low Blue Light (Hardware Solution)
- (Optional) TÜV Rheinland® Low Blue Light (Software Solution)<sup>[1]</sup>

---

#### Notes:

[1] TÜV Rheinland® Low Blue Light (Software Solution) certification is optional and only available on the models with preloaded OS.

- Feature with \*\* means that only one option listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS", WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.



Copilot+PC