

# ASUS BE249CGN

## Docking Monitor



Accessory slot for phone holder

PC mounted via mini PC kit

## Key Features



Optimized for the finest image and color quality with 178° wide-viewing-angle



120Hz refresh rate gives you so much more on top of the best smooth and quality for any content



DisplayPort

Extensive connectivity of USB-C, HDMI, DP in, DP out for daisy chain, USB hub and earphone jack



Daisy-chain

DisplayPort allows users to daisy chain for a multi-display setup from one video source.



USB Hub

Embedded USB3.2 hub (4 ports) for connecting mouse, keyboard, or other USB devices



USB Type-C

Full function USB-C connection for DisplayPort video, USB data transmission and supports up to 96W power delivery



RJ-45

Delivers stable Internet connection and one-cable docking to your laptop with RJ45 and USB-C connection



4-way Ergonomic Stand

Ergonomically-designed stand with tilt, swivel (+180° ~ -180°), pivot, and height adjustments



Wall Mountable

Space saving from compatible VESA mount standard (100 x 100 mm) and bundled ASUS miniPC kit(optional)



(By country)



The mark of responsible forestry



# Specification

Display	Panel Size(diagonal)	23.8" (60.45 cm) Wide Screen (16:9)
	Display Viewing Area(HxV)	527.04 x 296.46 mm
	Panel Type	IPS
	Display Surface	non-glare
	Color Saturation	99% sRGB
	True Resolution	1920x1080
	Pixel Pitch	0.2745 mm
	Brightness (Max.)	350cd/m <sup>2</sup>
	Contrast Ratio	3000:1(Max); 1500:1 (Typical)
	Viewing Angle (CR $\geq$ 10)	178°(H)/178°(V)
	Display Colors	16.7 million
	Refresh Rate	120Hz
	Response Time	5ms (GTG)
Features	Splendid™ Video Intelligence Tech.	Yes
	Color Temperature Selection	4 modes
	HDCP	Yes, 1.4
	HDR Support	HDR 10
	QuickFit	Yes
	VRR Technology	Yes (Adaptive-Sync)
	DisplayWidget	Yes, DisplayWidget Center
	ASUS Power Sync	Yes
Blue Light Filter	Yes	
Audio	Stereo Speaker	2W x 2 stereo, RMS
Input/ Output		USB-C (DP Alt mode with PD 96W), HDMI(v2.1) x 1 (TMDS), DisplayPort 1.4 in, DisplayPort output(for daisy-chain), USB3.2 Gen1 Type A x4 ports (downstream), Earphone jack , RJ45
Power	Power Consumption	<14.93 W <sup>*1</sup>
	Power Saving/Off Mode	<0.5W/ 0W(hard switch)
	Voltage	100-240V, 50 / 60 Hz
Mechanical Design	Chassis Colors	Black
	Tilt(angle)	+35° ~ -5°
	Swivel(angle)	+180° ~ -180°
	Pivot(angle/direction)	+90° ~ -90°
	Height Adjustment	0~150mm
VESA Wall Mounting	100x100mm	
Security	Kensington lock	Yes
Dimension	Phys. Dimension (WxHxD)	54.02 x 50.75 x 22.40 cm (21.27 x 19.98 x 8.82 inches)(highest with stand); 54.02 x 32.38 x 4.96 cm (21.27 x 12.75 x 1.95 inches)(w/o Stand)
	Box Dimension (WxHxD)	69.00 x 44.50 x 13.90 cm (27.17 x 17.52 x 5.47 inches)
Weight		Net Weight: 5.61 kg (12.37 lbs), Net Weight w/o Stand: 3.51 kg (7.74 lbs), Gross Weight: 8.30 kg (18.30 lbs)
Accessories (vary by regions)		Power Cord(1.8m), HDMI Cable(1.8m), USB-C Cable(optional), DisplayPort Cable (optional), Warranty Card, Quick Start Guide, MiniPC Kit (optional)
Compliance Standards		Energy Star, TCO, FCC, cTUVus, ICES-3, CB, CE, ErP, WEEE, TUV-GS, TUV-Ergo, ISO 9241-307, UkrSEPRO, CU, CCC, CECP, BSMI, RCM, AU MEPS, VCCI, PSE, PC Recycle, J-MOSS, KC, KCC, KMEPS, RoHS, CEC, WHQL Windows 10/11, EPEAT Gold(by country), TUV Flicker free, TUV Low Blue Light

\*1.Measuring a screen brightness of 200 nits without audio/ USB/ Card reader connection

\*.All specifications are subject to change without notice.