

MPG 272URX QD-OLED







SPECIFICATIONS

Panel Size	26.5"
Active Display Area (mm)	589.97 (H) x 332.93 (V)
Curvature	Flat
Panel Type	QD-OLED
Panel Resolution	3840x2160 (UHD)
Pixel Pitch (H x V)	0.153 (H) x 0.153 (V)
Aspect Ratio	16:9
Brightness (nits)	SDR: 250 HDR: 450 (Typ.) (True Black 400 with 10% APL) 1000 (Typ.) (Peak 1000 with 3% APL)
Contrast Ratio	1500000:1 (Typ.)
DCR	100000000:1
ACTIVATED RANGE	48~240Hz
Refresh Rate	240Hz
Response time	0.03ms (GtG)
DYNAMIC REFRESH RATE TECHNOLOGY	G-Sync Compatible
HDR Support	DisplayHDR True Black 400
Video ports	2x HDMI™ 2.1 (UHD@240Hz) 1x DisplayPort 2.1a (UHBR20) 1x Type-C (DP alt.) w/ 98W PD
USB ports	2x USB 5Gbps Type-A 1x USB 5Gbps Type-B
Audio ports	1x Headphone-out
Viewing Angle	178° (H) / 178° (V)
Adobe RGB / DCI-P3 / sRGB	98% / 99% / 138% (CIE1976 Standard)
Surface Treatment	Anti-glare
Display Colors	1.07B, 10 bits
Frameless Design	Yes
PIP / PBP Function	Yes
Power Type	Internal Power Board
Power Input	100~240V, 50/60Hz
Adjustment (Tilt)	-5° ~ 20°
Adjustment (Swivel)	-30° ~ 30°
Adjustment (Pivot)	-90° ~ 90°
Adjustment (Height)	0 ~ 110 mm
Kensington Lock	Yes

FEATURES



QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming



240Hz High Refresh Rate

Experience smooth gaming with a blazing-fast refresh rate, providing you with the upper hand in fast-moving games.



Fastest 0.03 Response time

Response time is much faster and smoother than conventional LCD displays. The response time is up to 0.03 ms GtG exceeds the most mainstream refresh rates requirements.



MSI has developed a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.



Gaming Intelligence

A new dawn of AI gaming, including Smart Brightness, Smart Crosshair, Night Vision AI, and Sound Tune.



USB Type-C Power Delivery 98W

Built-in an USB Type-C connection with 98W power delivery allows you to effortlessly connect to and charge your devices.



Graphene film with Custom Heatsink

Graphene film and customized heatsink designs, the synergy between these two elements enables monitor to operate without an active cooling fan, achieving a fanless design. This ensures efficient and silent heat dispersion, further extending the panel's



MONITORS

MPG 272URX QD-OLED

VESA Mounting	100 x 100 mm
Accessories	1x HDMI™ Cable (2.1) 1x DisplayPort Cable (2.1a) 1x Power Cord (C13) 1x Quick Guide 1x USB Type-B to A Cable 4x VESA Screw
Note	HDMI™: 3840 x 2160 (Up to 240Hz) DisplayPort: 3840 x 2160 (Up to 240Hz) Type-C: 3840 x 2160 (Up to 240Hz) Support: HDMI™ CEC, KVM, PIP/PBP
Warranty	3 years (including panel burn-in)

CONNECTIONS



- 1. Headphone-out
- 2. 2x HDMI[™] 2.1 (UHD@240Hz)
- 3. DisplayPort 2.1 (UHBR20)
- 4. USB Type-C (98W PD)
- 5. USB Type-B
- 6. 2x USB Type-A
- 7. 5-way Joystick Navigator
- 8. AC-in
- 9. Kensington lock