

# PRO MP275QPDG

BE YOUR WINDOW TO THE WORLD





### **SPECIFICATIONS**

PANEL RESOLUTION  REFRESH RATE  100Hz  RESPONSE TIME  1ms (MPRT) / 4ms (GTG)  PANEL TYPE  BRIGHTNESS (NITS)  250 cd/m2  VIEWING ANGLE  ASPECT RATIO  CONTRAST RATIO  ADOBE RGB / DCI-P3 / SRGB  ACTIVE DISPLAY AREA (MM)  PIXEL PITCH (H X V)  SUFFACE TREATMENT  DISPLAY COLORS  COLOR BIT  HDR Ready  2x HDMI™ 2.0b (WQHD@100Hz) 1x DisplayPort 1.2a input 1x DisplayPort 1.2a output 1x DisplayPort 1.2a output 1x DisplayPort 1.2a output 1x Type-C (DP alt.) w/ 98W PD  USB Ports  AUDIO PORTS  1x Headphone-out  KENSINGTON LOCK  SPEAKER  2x 2W  VESA MOUNTING  POWER TYPE  POWER INPUT  DYNAMIC REFRESH RATE TECHNOLOGY  ADJUSTMENT (HEIGHT)  DIMENSION (W X H X D)  CARTON DIMENSION (W X H X D)	PANEL SIZE	27"
RESPONSE TIME         1ms (MPRT) / 4ms (GTG)           PANEL TYPE         IPS           BRIGHTNESS (NITS)         250 cd/m2           VIEWING ANGLE         178°(H) / 178°(V)           ASPECT RATIO         16:9           CONTRAST RATIO         1300:1           ADOBE RGB / DCI-P3 / SRGB         84% / 79% / 100%           ACTIVE DISPLAY AREA (MM)         596.736(H) x 335.664(V)           PIXEL PITCH (H X V)         0.2331(H) x 0.2331(V)           SURFACE TREATMENT         Anti-glare           DISPLAY COLORS         1.07B           COLOR BIT         10 bits (8 bits + FRC)           HDR Ready         2x HDMI™ 2.0b (WQHD@100Hz)           1x DisplayPort 1.2a output         1x DisplayPort 1.2a output           1x Type-C (DP alt.) w/ 98W PD           USB Ports         1x USB 5Gbps Type-B           4x USB 5Gbps Type-B         4x USB 5Gbps Type-B           4x USB 5Gbps Type-B<	PANEL RESOLUTION	2560 x 1440 (WQHD)
PANEL TYPE         IPS           BRIGHTNESS (NITS)         250 cd/m2           VIEWING ANGLE         178°(H) / 178°(V)           ASPECT RATIO         16:9           CONTRAST RATIO         1300:1           ADDBE RGB / DCI-P3 / SRGB         84% / 79% / 100%           ACTIVE DISPLAY AREA (MM)         596.736(H) x 335.664(V)           PIXEL PITCH (H X V)         0.2331(H) x 0.2331(V)           SURFACE TREATMENT         Anti-glare           DISPLAY COLORS         1.07B           COLOR BIT         10 bits (8 bits + FRC)           HDR Ready         2x HDMI™ 2.0b (WQHD@100Hz)           VIDEO PORTS         1x DisplayPort 1.2a input 1x DisplayPort 1.2a output 1x Type-C (DP alt.) w/ 98W PD           USB Ports         1x USB 5Gbps Type-B 4x USB 5Gbps Type-B 4x USB 5Gbps Type-A           AUDIO PORTS         1x Headphone-out           KENSINGTON LOCK         Yes           SPEAKER         2x 2W           VESA MOUNTING         100 x 100 mm           POWER TYPE         Internal Power Board           POWER TYPE         Internal Power Board           POWER TYPE         Adaptive-Sync           ADJUSTMENT (TILT)         -5° ~ 20°           ADJUSTMENT (FIVOT)         -90° ~ 90°           ADJUSTMENT (HEIGHT)	REFRESH RATE	100Hz
BRIGHTNESS (NITS)         250 cd/m2           VIEWING ANGLE         178°(H) / 178°(V)           ASPECT RATIO         16:9           CONTRAST RATIO         1300:1           ADOBE RGB / DCI-P3 / SRGB         84% / 79% / 100%           ACTIVE DISPLAY AREA (MM)         596.736(H) x 335.664(V)           PIXEL PITCH (H X V)         0.2331(H) x 0.2331(V)           SURFACE TREATMENT         Anti-glare           DISPLAY COLORS         1.07B           COLOR BIT         10 bits (8 bits + FRC)           HDR Ready         2x HDMI™ 2.0b (WQHD@100Hz)           1x DisplayPort 1.2a input         1x DisplayPort 1.2a output           1x Type-C (DP alt.) w/ 98W PD         1x USB FGbps Type-B           4x USB FGbps Type-B         4x USB FGbps Type-A           4x USB FGbps Type-A         1x Headphone-out           KENSINGTON LOCK         Yes           SPEAKER         2x 2W           VESA MOUNTING         100 x 100 mm           POWER TYPE         Internal Power Board           POWER INPUT         100 ~ 240V, 50~60Hz           DYNAMIC REFRESH RATE TECHNOLOGY         Adaptive-Sync           ADJUSTMENT (TILT)         -5° ~ 20°           ADJUSTMENT (FIVOT)         -90° ~ 90°           ADJUSTMENT (HEIGHT)         0 ~	RESPONSE TIME	1ms (MPRT) / 4ms (GTG)
VIEWING ANGLE         178°(H) / 178°(V)           ASPECT RATIO         16:9           CONTRAST RATIO         1300:1           ADOBE RGB / DCI-P3 / SRGB         84% / 79% / 100%           ACTIVE DISPLAY AREA (MM)         596.736(H) x 335.664(V)           PIXEL PITCH (H X V)         0.2331(H) x 0.2331(V)           SURFACE TREATMENT         Anti-glare           DISPLAY COLORS         1.07B           COLOR BIT         10 bits (8 bits + FRC)           HDR Ready         2x HDMI™ 2.0b (WQHD@100Hz)           1x DisplayPort 1.2a input         1x DisplayPort 1.2a output           1x Type-C (DP alt.) w/ 98W PD         1x USB 5Gbps Type-B           4x USB 5Gbps Type-B         4x USB 5Gbps Type-B           4x USB 5Gbps Type-A         4x USB 5Gbps Type-A           AUDIO PORTS         1x Headphone-out           KENSINGTON LOCK         Yes           SPEAKER         2x 2W           VESA MOUNTING         100 x 100 mm           POWER TYPE         Internal Power Board           POWER INPUT         100~240V, 50~60Hz           DYNAMIC REFRESH RATE         Adaptive-Sync           ADJUSTMENT (TILT)         -5° ~ 20°           ADJUSTMENT (PIVOT)         -90° ~ 90°           ADJUSTMENT (HEIGHT)         0 ~ 130 mm </th <th>PANEL TYPE</th> <th>IPS</th>	PANEL TYPE	IPS
ASPECT RATIO  CONTRAST RATIO  ADOBE RGB / DCI-P3 / SRGB  ACTIVE DISPLAY AREA (MM)  PIXEL PITCH (H X V)  SURFACE TREATMENT  DISPLAY COLORS  COLOR BIT  HDR Ready  VIDEO PORTS  USB Ports  1x DisplayPort 1.2a output 1x Type-C (DP alt.) w/ 98W PD  USB Ports  LX USB 5Gbps Type-B 4x USB 5Gbps Type-A  AUDIO PORTS  XENSINGTON LOCK  SPEAKER  VESA MOUNTING  POWER TYPE  INTERIOR  POWER INPUT  DYNAMIC REFRESH RATE TECHNOLOGY  ADJUSTMENT (TILT)  ADJUSTMENT (FIVOT)  ADJUSTMENT (PIVOT)  ADJUSTMENT (HEIGHT)  DIMENSION (W X H X D)  831 x 468 x 133 mm  POWER 133 3 mm  1.300:1  300	BRIGHTNESS (NITS)	250 cd/m2
CONTRAST RATIO       1300:1         ADOBE RGB / DCI-P3 / SRGB       84% / 79% / 100%         ACTIVE DISPLAY AREA (MM)       596.736(H) x 335.664(V)         PIXEL PITCH (H X V)       0.2331(H) x 0.2331(V)         SURFACE TREATMENT       Anti-glare         DISPLAY COLORS       1.07B         COLOR BIT       10 bits (8 bits + FRC)         HDR Ready       2x HDMI™ 2.0b (WQHD@100Hz)         1x DisplayPort 1.2a input 1x DisplayPort 1.2a input 1x Type-C (DP alt.) w/ 98W PD         USB Ports       1x USB 5Gbps Type-B 4x USB 5Gbps Type-B 4x USB 5Gbps Type-A         AUDIO PORTS       1x Headphone-out         KENSINGTON LOCK       Yes         SPEAKER       2x 2W         VESA MOUNTING       100 x 100 mm         POWER TYPE       Internal Power Board         POWER INPUT       100~240V, 50~60Hz         DYNAMIC REFRESH RATE TECHNOLOGY       Adaptive-Sync         ADJUSTMENT (TILT)       -5° ~ 20°         ADJUSTMENT (FIVOT)       -90° ~ 90°         ADJUSTMENT (PIVOT)       -90° ~ 233.9 mm (24.2 x 22.8 x 9.2 inch)         BASTA Y 468 x 133 mm	VIEWING ANGLE	178°(H) / 178°(V)
ADOBE RGB / DCI-P3 / SRGB  ACTIVE DISPLAY AREA (MM)  PIXEL PITCH (H X V)  SURFACE TREATMENT  DISPLAY COLORS  COLOR BIT  HDR Ready  2x HDMI™ 2.0b (WQHD@100Hz) 1x DisplayPort 1.2a input 1x DisplayPort 1.2a input 1x DisplayPort 1.2a output 1x Type-C (DP alt.) w/ 98W PD  USB Ports  1x USB 5Gbps Type-B 4x USB 5Gbps Type-B 4x USB 5Gbps Type-A  AUDIO PORTS  1x Headphone-out  KENSINGTON LOCK  YES  SPEAKER  2x 2W  VESA MOUNTING  POWER INPUT  DYNAMIC REFRESH RATE TECHNOLOGY  ADJUSTMENT (TILT)  ADJUSTMENT (SWIVEL)  ADJUSTMENT (PIVOT)  ADJUSTMENT (HEIGHT)  DIMENSION (W X H X D)  831 x 468 x 133 mm  831 x 468 x 133 mm  831 x 468 x 133 mm	ASPECT RATIO	16:9
ACTIVE DISPLAY AREA (MM)  PIXEL PITCH (H X V)  SURFACE TREATMENT  DISPLAY COLORS  COLOR BIT  HDR Ready  2x HDMI™ 2.0b (WQHD@100Hz) 1x DisplayPort 1.2a input 1x Type-C (DP alt.) w/ 98W PD  USB Ports  AUDIO PORTS  LX USB 5Gbps Type-B 4x USB 5Gbps Type-A  AUDIO PORTS  ENSINGTON LOCK  SPEAKER  VESA MOUNTING  POWER TYPE  Internal Power Board  POWER INPUT  DYNAMIC REFRESH RATE TECHNOLOGY  ADJUSTMENT (TILT)  ADJUSTMENT (PIVOT)  ADJUSTMENT (PIVOT)  ADJUSTMENT (HEIGHT)  DYNAMIC REFRESH (MM)  596.736(H) x 335.664(V) 0.2331(H) x 0.2331(V)  Anti-glare 1.07B  1	CONTRAST RATIO	1300:1
PIXEL PITCH (H X V)         0.2331(H) x 0.2331(V)           SURFACE TREATMENT         Anti-glare           DISPLAY COLORS         1.07B           COLOR BIT         10 bits (8 bits + FRC)           HDR Ready         2x HDMI™ 2.0b (WQHD@100Hz)           1x DisplayPort 1.2a input 1x DisplayPort 1.2a input 1x DisplayPort 1.2a output 1x Type-C (DP alt.) w/ 98W PD           USB Ports         1x USB 5Gbps Type-B 4x USB 5Gbps Type-B 4x USB 5Gbps Type-A           AUDIO PORTS         1x Headphone-out           KENSINGTON LOCK         Yes           SPEAKER         2x 2W           VESA MOUNTING         100 x 100 mm           POWER TYPE         Internal Power Board           POWER INPUT         100~240V, 50~60Hz           DYNAMIC REFRESH RATE TECHNOLOGY         Adaptive-Sync           ADJUSTMENT (TILT)         -5° ~ 20°           ADJUSTMENT (SWIVEL)         -45° ~ 45°           ADJUSTMENT (PIVOT)         -90° ~ 90°           ADJUSTMENT (HEIGHT)         0 ~ 130 mm           DIMENSION (W X H X D)         831 x 468 x 133 mm	ADOBE RGB / DCI-P3 / SRGB	84% / 79% / 100%
SURFACE TREATMENT DISPLAY COLORS  COLOR BIT  10 bits (8 bits + FRC)  HDR Ready  2x HDMI™ 2.0b (WQHD@100Hz) 1x DisplayPort 1.2a input 1x Type-C (DP alt.) w/ 98W PD  USB Ports  1x USB 5Gbps Type-B 4x USB 5Gbps Type-A  AUDIO PORTS  1x Headphone-out  KENSINGTON LOCK Yes  SPEAKER  2x 2W  VESA MOUNTING 100 x 100 mm  POWER TYPE Internal Power Board  POWER INPUT 100~240V, 50~60Hz  ADJUSTMENT (TILT) ADJUSTMENT (SWIVEL) ADJUSTMENT (PIVOT) ADJUSTMENT (HEIGHT)  DIMENSION (W X H X D)  831 x 468 x 133 mm   CARTON DIMENSION (W X H X D)  831 x 468 x 133 mm	ACTIVE DISPLAY AREA (MM)	596.736(H) x 335.664(V)
DISPLAY COLORS       1.07B         COLOR BIT       10 bits (8 bits + FRC)         HDR SUPPORT       HDR Ready         2x HDMI™ 2.0b (WQHD@100Hz)       1x DisplayPort 1.2a input 1x DisplayPort 1.2a output 1x Type-C (DP alt.) w/ 98W PD         USB Ports       1x USB 5Gbps Type-B 4x USB 5Gbps Type-B 4x USB 5Gbps Type-A         AUDIO PORTS       1x Headphone-out         KENSINGTON LOCK       Yes         SPEAKER       2x 2W         VESA MOUNTING       100 x 100 mm         POWER TYPE       Internal Power Board         POWER INPUT       100~240V, 50~60Hz         DYNAMIC REFRESH RATE TECHNOLOGY       Adaptive-Sync         ADJUSTMENT (TILT)       -5° ~ 20°         ADJUSTMENT (PIVOT)       -90° ~ 90°         ADJUSTMENT (HEIGHT)       0 ~ 130 mm         DIMENSION (W X H X D)       831 x 468 x 133 mm	PIXEL PITCH (H X V)	0.2331(H) x 0.2331(V)
COLOR BIT         10 bits (8 bits + FRC)           HDR SUPPORT         HDR Ready           VIDEO PORTS         2x HDMI™ 2.0b (WQHD@100Hz)           1x DisplayPort 1.2a input         1x DisplayPort 1.2a output           1x Type-C (DP alt.) w/ 98W PD           USB Ports         1x USB 5Gbps Type-B           4x USB 5Gbps Type-A           AUDIO PORTS         1x Headphone-out           KENSINGTON LOCK         Yes           SPEAKER         2x 2W           VESA MOUNTING         100 x 100 mm           POWER TYPE         Internal Power Board           POWER INPUT         100~240V, 50~60Hz           DYNAMIC REFRESH RATE TECHNOLOGY         Adaptive-Sync           ADJUSTMENT (TILT)         -5° ~ 20°           ADJUSTMENT (PIVOT)         -90° ~ 90°           ADJUSTMENT (HEIGHT)         0 ~ 130 mm           DIMENSION (W X H X D)         831 x 468 x 133 mm	SURFACE TREATMENT	Anti-glare
HDR SUPPORT    ADDITION   CARTON DIMENSION (W X H X D)	DISPLAY COLORS	1.07B
VIDEO PORTS  2x HDMI™ 2.0b (WQHD@100Hz) 1x DisplayPort 1.2a input 1x DisplayPort 1.2a output 1x Type-C (DP alt.) w/ 98W PD  1x USB 5Gbps Type-B 4x USB 5Gbps Type-A  AUDIO PORTS  1x Headphone-out  KENSINGTON LOCK Yes  SPEAKER  2x 2W  VESA MOUNTING  100 x 100 mm  POWER TYPE  Internal Power Board  POWER INPUT  100~240V, 50~60Hz  DYNAMIC REFRESH RATE TECHNOLOGY  ADJUSTMENT (TILT)  ADJUSTMENT (SWIVEL)  ADJUSTMENT (PIVOT)  ADJUSTMENT (HEIGHT)  DIMENSION (W X H X D)  2x HDMI™ 2.0b (WQHD@100Hz) 1x DisplayPort 1.2a input 1x DisplayPort 1.2a	COLOR BIT	10 bits (8 bits + FRC)
VIDEO PORTS         1x DisplayPort 1.2a input 1x DisplayPort 1.2a output 1x Type-C (DP alt.) w/ 98W PD           USB Ports         1x USB 5Gbps Type-B 4x USB 5Gbps Type-A           AUDIO PORTS         1x Headphone-out           KENSINGTON LOCK         Yes           SPEAKER         2x 2W           VESA MOUNTING         100 x 100 mm           POWER TYPE         Internal Power Board           POWER INPUT         100~240V, 50~60Hz           DYNAMIC REFRESH RATE TECHNOLOGY         Adaptive-Sync           ADJUSTMENT (TILT)         -5° ~ 20°           ADJUSTMENT (SWIVEL)         -45° ~ 45°           ADJUSTMENT (HEIGHT)         0 ~ 130 mm           DIMENSION (W X H X D)         614.0 x 578.9 x 233.9 mm (24.2 x 22.8 x 9.2 inch)           831 x 468 x 133 mm	HDR SUPPORT	HDR Ready
AUDIO PORTS  AUDIO PORTS  Ix Headphone-out  XENSINGTON LOCK  Yes  SPEAKER  VESA MOUNTING  POWER TYPE  Internal Power Board  POWER INPUT  DYNAMIC REFRESH RATE TECHNOLOGY  ADJUSTMENT (TILT)  ADJUSTMENT (SWIVEL)  ADJUSTMENT (PIVOT)  ADJUSTMENT (HEIGHT)  DIMENSION (W X H X D)  AUDIO TO THE AUDI	VIDEO PORTS	1x DisplayPort 1.2a input 1x DisplayPort 1.2a output
KENSINGTON LOCK         Yes           SPEAKER         2x 2W           VESA MOUNTING         100 x 100 mm           POWER TYPE         Internal Power Board           POWER INPUT         100~240V, 50~60Hz           DYNAMIC REFRESH RATE         Adaptive-Sync           ADJUSTMENT (TILT)         -5° ~ 20°           ADJUSTMENT (SWIVEL)         -45° ~ 45°           ADJUSTMENT (PIVOT)         -90° ~ 90°           ADJUSTMENT (HEIGHT)         0 ~ 130 mm           DIMENSION (W X H X D)         614.0 x 578.9 x 233.9 mm (24.2 x 22.8 x 9.2 inch)           831 x 468 x 133 mm	USB Ports	
SPEAKER         2x 2W           VESA MOUNTING         100 x 100 mm           POWER TYPE         Internal Power Board           POWER INPUT         100~240V, 50~60Hz           DYNAMIC REFRESH RATE         Adaptive-Sync           ADJUSTMENT (TILT)         -5° ~ 20°           ADJUSTMENT (SWIVEL)         -45° ~ 45°           ADJUSTMENT (PIVOT)         -90° ~ 90°           ADJUSTMENT (HEIGHT)         0 ~ 130 mm           DIMENSION (W X H X D)         614.0 x 578.9 x 233.9 mm (24.2 x 22.8 x 9.2 inch)           831 x 468 x 133 mm	AUDIO PORTS	1x Headphone-out
VESA MOUNTING         100 x 100 mm           POWER TYPE         Internal Power Board           POWER INPUT         100~240V, 50~60Hz           DYNAMIC REFRESH RATE TECHNOLOGY         Adaptive-Sync           ADJUSTMENT (TILT)         -5° ~ 20°           ADJUSTMENT (SWIVEL)         -45° ~ 45°           ADJUSTMENT (PIVOT)         -90° ~ 90°           ADJUSTMENT (HEIGHT)         0 ~ 130 mm           DIMENSION (W X H X D)         614.0 x 578.9 x 233.9 mm (24.2 x 22.8 x 9.2 inch)           831 x 468 x 133 mm	KENSINGTON LOCK	Yes
POWER TYPE         Internal Power Board           POWER INPUT         100~240V, 50~60Hz           DYNAMIC REFRESH RATE TECHNOLOGY         Adaptive-Sync           ADJUSTMENT (TILT)         -5° ~ 20°           ADJUSTMENT (SWIVEL)         -45° ~ 45°           ADJUSTMENT (PIVOT)         -90° ~ 90°           ADJUSTMENT (HEIGHT)         0 ~ 130 mm           DIMENSION (W X H X D)         614.0 x 578.9 x 233.9 mm (24.2 x 22.8 x 9.2 inch)           831 x 468 x 133 mm	SPEAKER	2x 2W
POWER INPUT         100~240V, 50~60Hz           DYNAMIC REFRESH RATE TECHNOLOGY         Adaptive-Sync           ADJUSTMENT (TILT)         -5° ~ 20°           ADJUSTMENT (SWIVEL)         -45° ~ 45°           ADJUSTMENT (PIVOT)         -90° ~ 90°           ADJUSTMENT (HEIGHT)         0 ~ 130 mm           DIMENSION (W X H X D)         614.0 x 578.9 x 233.9 mm (24.2 x 22.8 x 9.2 inch)           831 x 468 x 133 mm	VESA MOUNTING	100 x 100 mm
DYNAMIC REFRESH RATE TECHNOLOGY         Adaptive-Sync           ADJUSTMENT (TILT)         -5° ~ 20°           ADJUSTMENT (SWIVEL)         -45° ~ 45°           ADJUSTMENT (PIVOT)         -90° ~ 90°           ADJUSTMENT (HEIGHT)         0 ~ 130 mm           DIMENSION (W X H X D)         614.0 x 578.9 x 233.9 mm (24.2 x 22.8 x 9.2 inch)           831 x 468 x 133 mm	POWER TYPE	Internal Power Board
TECHNOLOGY         Adaptive-sync           ADJUSTMENT (TILT)         -5° ~ 20°           ADJUSTMENT (SWIVEL)         -45° ~ 45°           ADJUSTMENT (PIVOT)         -90° ~ 90°           ADJUSTMENT (HEIGHT)         0 ~ 130 mm           DIMENSION (W X H X D)         614.0 x 578.9 x 233.9 mm (24.2 x 22.8 x 9.2 inch)           831 x 468 x 133 mm	POWER INPUT	100~240V, 50~60Hz
ADJUSTMENT (SWIVEL)  ADJUSTMENT (PIVOT)  ADJUSTMENT (HEIGHT)  O ~ 130 mm  DIMENSION (W X H X D)  614.0 x 578.9 x 233.9 mm (24.2 x 22.8 x 9.2 inch)  831 x 468 x 133 mm		Adaptive-Sync
ADJUSTMENT (PIVOT) -90° ~ 90°  ADJUSTMENT (HEIGHT) 0 ~ 130 mm  DIMENSION (W X H X D) 614.0 x 578.9 x 233.9 mm (24.2 x 22.8 x 9.2 inch)  CARTON DIMENSION (W X H X D) 831 x 468 x 133 mm	ADJUSTMENT (TILT)	-5° ~ 20°
ADJUSTMENT (HEIGHT)  DIMENSION (W X H X D)  CARTON DIMENSION (W X H X D)  0 ~ 130 mm  614.0 x 578.9 x 233.9 mm  (24.2 x 22.8 x 9.2 inch)  831 x 468 x 133 mm	ADJUSTMENT (SWIVEL)	-45° ~ 45°
DIMENSION (W X H X D)  614.0 x 578.9 x 233.9 mm (24.2 x 22.8 x 9.2 inch)  831 x 468 x 133 mm	ADJUSTMENT (PIVOT)	-90° ~ 90°
(24.2 x 22.8 x 9.2 inch)  (ARTON DIMENSION (W X H X D)  831 x 468 x 133 mm	ADJUSTMENT (HEIGHT)	0 ~ 130 mm
CARTON DIMENSION (W X H X D)	DIMENSION (W X H X D)	
	CARTON DIMENSION (W X H X D)	

## **FEATURES**



#### **Docking Monitor**

Enhance your workspace with a docking monitor. Simplify connectivity, switch between tasks seamlessly, and boost productivity—all with a single monitor.



Simplify setup and streamline connectivity with daisy-chaining. Connect multiple monitors effortlessly for a more organized and productive workspace.



#### **IPS Grade Panel**

Instantly optimize the screen colors and brightness to ensure that you enjoy every detail at its best while creating your own on-line video



# **Webcam Cover**

Safely Connect to the world with a webcam cover.



#### EyesErgo

EyesErgo An eye care solution designed with ergonomics in mind.



#### Productivity Intelligence App (P.I.)

The Productivity Intelligence App (P.I.) provides the smartest tool, KVM function, color & display mode to you while working with it every day



Control multiple devices via one set of keyboard, mouse, and MSI gaming monitor.



### **Adjustable Stand**

Adjust the stand to the angle that is most suitable for you to keep yourself work comfortably.



#### 100Hz High Refresh Rate

100 Hz Experience smooth gaming with a blazing fast 100Hz refresh rate, that gives you the upperhand in fast moving games.



# PRO MP275QPDG

BE YOUR WINDOW TO THE WORLD

WEIGHT (NW / GW)	7.05 kg (16.53 lbs) / 10.24 kg (22.58 lbs)
CERTIFICATES	CB/CE Energy Star
VIDEO INPUT COMPATIBILITY	PC, Mac, PS5 <sup>™</sup> , PS4 <sup>™</sup> , Xbox, Mobile, Notebook * All trademarks and the registered trademarks are the property of their respective owners.
ACCESSORIES	1x HDMI™ Cable (2.0), 1x USB Type-C Cable, 1x USB Type-B to A cable, 1x Power Cord, 1x Quick Guide, 4x Stand Screw, 1x VESA Plate, 4x VESA Plate Screws
Note	HDMI™: 2560 x 1440 (Up to 100Hz) DisplayPort: 2560 x 1440 (Up to 100Hz) Type-C (DP Alt.): 2560 x 1440 (Up to 100Hz) w/ 98W PD HDMI™ CEC Support *Adobe RGB, DCI-P3 and sRGB follow CIE1976 Standard

# **CONNECTIONS**



- 1. DC-Jack
- 2. 2x HDMI<sup>™</sup> 2.0b (WQHD@100Hz)
- 3. 1x DisplayPort 1.2a Input
- 4. 1x Type-C (DP Alt.) w/ 98W
- 5. 1x DisplayPort 1.2a Output
- 6. 1x USB 5Gbps Type-B
- 7. 1x LAN Port
- 8. 4x USB 5Gbps Type-A
- 9. Headphone-out
- 10. 1x Kensington Lock
- 11. 5-Way Navigator