

# **OVERVIEW**



1. Smart card reader *	6. 2x Thunderbolt 4
2. Nano-SIM card slot *	7. HDMI
3. USB-A (USB 5Gbps)	8. USB-A (USB 5Gbps), Always On
4. Ethernet (RJ-45)	9. Headphone / microphone combo jack (3.5mm)
5. Kensington Nano Security Slot	

#### Notes

• Items with \* are only available on selected models



# **PERFORMANCE**

### **Processor**

### **Processor Family**

Intel® U or H Series Core Ultra 5 / 7 Processor (Series 1)

### Processor\*\*

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Processor Graphics	NPU
Core Ultra 5 125H	14 (4 P-core + 8 E-core + 2 LPE- core)				18MB	Intel® Arc™ Graphics <sup>[1]</sup>	Intel® AI Boost
Core Ultra 5 125U	12 (2 P-core + 8 E-core + 2 LPE- core)	14	P-core 1.3GHz / E-core 800MHz / LPE-core 700MHz	P-core 4.3GHz / E-core 3.6GHz / LPE-core 2.1GHz	12MB	Intel® Graphics	Intel® AI Boost
Core Ultra 5 135H	14 (4 P-core + 8 E-core + 2 LPE- core)	18	P-core 1.7GHz / E-core 1.2GHz / LPE-core 700MHz	P-core 4.6GHz / E-core 3.6GHz / LPE-core 2.5GHz	18MB	Intel® Arc™ Graphics[2]	Intel® AI Boost
Core Ultra 5 135U	12 (2 P-core + 8 E-core + 2 LPE- core)	14	P-core 1.6GHz / E-core 1.1GHz / LPE-core 700MHz	P-core 4.4GHz / E-core 3.6GHz / LPE-core 2.1GHz	12MB	Intel® Graphics	Intel® AI Boost
Core Ultra 7 155H	16 (6 P-core + 8 E-core + 2 LPE- core)	22	P-core 1.4GHz / E-core 900MHz / LPE-core 700MHz	P-core 4.8GHz / E-core 3.8GHz / LPE-core 2.5GHz	24MB	Intel® Arc™ Graphics[3]	Intel® AI Boost
Core Ultra 7 155U	12 (2 P-core + 8 E-core + 2 LPE- core)	14	P-core 1.7GHz / E-core 1.2GHz / LPE-core 700MHz	P-core 4.8GHz / E-core 3.8GHz / LPE-core 2.1GHz	12MB	Intel® Graphics	Intel® AI Boost
Core Ultra 7 165H	16 (6 P-core + 8 E-core + 2 LPE- core)	22	P-core 1.4GHz / E-core 900MHz / LPE-core 700MHz	P-core 5.0GHz / E-core 3.8GHz / LPE-core 2.5GHz	24MB	Intel® Arc™ Graphics <sup>[4]</sup>	Intel® AI Boost
Core Ultra 7 165U	12 (2 P-core + 8 E-core + 2 LPE- core)	14	P-core 1.7GHz / E-core 1.2GHz / LPE-core 700MHz	P-core 4.9GHz / E-core 3.8GHz / LPE-core 2.1GHz	12MB	Intel® Graphics	Intel® AI Boost

#### Notes:

[1], [2], [3], [4] Intel® Arc™ Graphics only available on select H-series Intel® Core™ Ultra processor powered systems with at least 16GB of system memory in a dual-channel configurations, otherwise it will function as Intel® Graphics.

# Al (Artificial Intelligence)

**AI PC Category** 

AI PC

Integrated Intel® AI Boost, up to 11 TOPS

# **Operating System**

### Operating System\*\*

- Windows® 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- Windows® 11 IoT Enterprise LTSC 2024
- Windows® 11 DG Windows® 10 Pro 64<sup>[1]</sup>
- Windows® 10 IoT Enterprise LTSC 2021
- Fedora Linux<sup>[2]</sup>
- Ubuntu Linux<sup>[3]</sup>
- Linux<sup>[4]</sup>
- · No preload operating system



#### Notes:

[1] Windows® 11 DG Windows® 10 Pro 64 is for special bid only.

[2], [3], [4] Some features may not be supported on the system with Linux preload, including but not limited to Intel® RST RAID, MIPI computer vision camera, WWAN, Human Presence Detection, etc.

## **Graphics**

## Graphics\*\*

Graphics	Туре	Memory	Key Features
Intel® Arc™ Graphics <sup>[1]</sup>	Integrated	Shared	DirectX® 12.2
Intel® Graphics	Integrated	Shared	DirectX® 12.1

### Notes:

[1] Intel® Arc™ Graphics only available on select H-series Intel® Core™ Ultra processor powered systems with at least 16GB of system memory in a dual-channel configurations, otherwise it will function as Intel® Graphics.

## **Monitor Support**

### Monitor Support[1]

Supports up to 4 independent displays (native display and 3 external monitors via HDMI® and Thunderbolt™)

- HDMI® supports up to 4K@60Hz
- Thunderbolt™ supports up to 8K@60Hz<sup>[2]</sup>

#### Notes:

[1] Refresh rates >60hz also supported, however max resolution will be limited.

[2] 8K resolution support needs 2 display pipes. That is, simultaneous display number will "-1" when 8K resolution displayed.

## **Chipset**

### Chipset

Intel® SoC (System on Chip) platform

### Memory

### **Max Memory**

Up to 64GB DDR5-5600

#### **Memory Slots**

Two DDR5 SO-DIMM slots, dual-channel capable

### **Memory Type**

DDR5-5600

### **Storage**

#### Storage Support[1]

One drive, up to 2TB M.2 2280 SSD

### **Storage Slot**

One M.2 2280 PCIe® 4.0 x4 slot

#### Storage Type\*\*

Disk Type	Interface	Offering	Security
M.2 2280 SSD	PCIe® NVMe®, PCIe® 4.0 x4	256GB / 512GB / 1TB	Opal 2.0
M.2 2280 SSD	PCIe® NVMe®, PCIe® 4.0 x4 Performance	512GB / 1TB / 2TB	Opal 2.0

#### Notes:

[1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.

### **Removable Storage**

### Card Reader



No card reader

# Multi-Media

#### **Audio Chip**

High Definition (HD) Audio, Realtek® ALC3287 codec

### **Speakers**

Stereo speakers, 2W x2, Dolby Audio™

#### Microphone

- Dual-microphone array, 360° far-field, Dolby Voice®
- No microphone

#### Camera\*\*

- 5.0MP + IR discrete, with privacy shutter, fixed focus, temporal noise reduction
- 5.0MP, with privacy shutter, fixed focus, temporal noise reduction
- No camera<sup>[1]</sup>

Notes:

[1] No camera is for special bid only.

### **Battery**

### Battery\*\*[1]

- Integrated Li-Polymer 39.3Wh battery, supports Rapid Charge (charge up to 80% in 1hr) with 65W AC adapter[2]
- Integrated Li-Polymer 52.5Wh battery, supports Rapid Charge (charge up to 80% in 1hr) with 65W AC adapter

#### Battery Life[3]

Configuration 1 (max battery life)

MobileMark® 25: up to 11.5 hr with 600 performance score @250nits JEITA-BAT 3.0 (Video/Idle): up to 10.7 hr / 24.8 hr @200nits Local video playback: up to 20.7 hr @150nits

Alternate configuration 2

MobileMark $^{\circ}$  25: up to 11.2 hr with 666 performance score @250nits JEITA-BAT 3.0 (Video/Idle): up to 10.9 hr / 24.1 hr @200nits Local video playback: up to 20.0 hr @150nits

Alternate configuration 3

MobileMark® 25: up to 10.5 hr with 637 performance score @250nits JEITA-BAT 3.0 (Video/Idle): up to 8.9 hr / 19.8 hr @200nits Local video playback: up to 18.1 hr @150nits

#### Notes:

[1] Rapid charge is only guaranteed when the computer is turned off or in standby mode or in hibernation mode. When the computer is powered on, the Charge Time will vary depending on system power consumption and AC adapter power.
[2] 39.3Wh battery is for special bid only.

[3] Configuration 1 (max battery life): WUXGA low power (non-touch), Intel® Core™ Ultra 5 125U, 8GB DDR5, Win 11, 52.5Wh battery, best power efficiency power mode

Alternate configuration 2: WUXGA low power (non-touch), Intel® Core™ Ultra 5 125H, 8GB DDR5, Win 11, 52.5Wh battery, best power efficiency power mode

Alternate configuration 3: WUXGA (non-touch), Intel $^{\circ}$  Core $^{\mathsf{TM}}$  Ultra 5 135U, 16GB DDR5, Win 11, 52.5Wh battery, best power efficiency power mode

All battery life claims are approximate maximum and based on results using MobileMark® 25, JEITA 3.0, continuous 1080p local video playback (using default Media Player in Fullscreen mode with 150nits brightness and default volume level), or Google Power Load Test (PLT) battery-life benchmark tests.

Actual battery life will vary depending on many factors such as product configuration, software, wireless functionality, power management settings, and screen brightness.

The maximum capacity of the battery will decrease with time, ambient temperature and use.

Refer to Microsoft® link for more information about the Windows® Performance power slider.

### **Power Adapter**

Power Adapter\*\*[1]



- 45W USB-C<sup>®</sup> (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 45W USB-C<sup>®</sup> (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- \* 65W USB-C $^{\circ}$  (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C $^{\circ}$  slim (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® slim (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- No power adapter<sup>[2]</sup>

#### Notes:

- [1] AC adapter offerings depend on the country.
- [2] No power adapter is for special bid only.

### **DESIGN**

# **Display**

### Display\*\*[1]

Size	Resolution	Touch	Туре	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Refresh Rate	Viewing Angle (L/R/U/D)	Key Features
14"	WUXGA (1920x1200)	None	IPS <sup>[2]</sup>	400nits	Anti-glare	16:10	1000:1	45% NTSC	60Hz	89° / 89° / 89° / 89°	85.73% screen to body ratio, 3M™ DBEF5
14"	WUXGA (1920x1200)	Multi- touch	IPS <sup>[3]</sup>	400nits	Anti-glare	16:10	1000:1	45% NTSC	60Hz	89° / 89° /	Eyesafe® Certified 2.0, 85.73% screen to body ratio, 3M™ DBEF5
14"	WUXGA (1920x1200)	None	IPS <sup>[4]</sup>	400nits	Anti-glare	16:10	1000:1	100% sRGB	60Hz	85° / 85° / 85° / 85°	Low power, Eyesafe® Certified 2.0, 85.73% screen to body ratio
14"	WUXGA (1920x1200)	Multi- touch	IPS <sup>[5]</sup>	500nits	Anti-glare	16:10	1500:1	100% sRGB	60Hz	89° / 89° / 89° / 89°	ThinkPad® Privacy Guard, 85.73% screen to body ratio
14"	2.2K (2240x1400)	None	IPS <sup>[6]</sup>	300nits	Anti-glare	16:10	1500:1	100% sRGB	60Hz	85° / 85° / 85° / 85°	TÜV Low Blue Light (Hardware Solution), 85.73% screen to body ratio
14"	2.8K (2880x1800)	None	OLED	400nits	Anti-glare, anti- reflection, anti- smudge	16:10	100,000:1	100% DCI- P3	120Hz	85° / 85° / 85° / 85°	DisplayHDR™ True Black 500, Dolby Vision®, Eyesafe® Certified 2.0, 85.73% screen to body ratio

### Touchscreen

- On-cell multi-touch, supports 10-point touch
- Non-touch

### Notes:

[1] 3M™ DBEF5 (Dual Brightness Enhancement Film) improves the experience with higher brightness and lower energy. [2], [3], [4], [5], [6] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.



## **Input Device**

#### Pen

No support

### Keyboard

6-row, spill-resistant, multimedia Fn keys, Copilot key

### **Keyboard Backlight**

- · LED backlight
- · Non-backlight

#### UltraNav™

TrackPoint® pointing device, double-tap to open the TrackPoint® Quick Menu Glass-like Mylar® surface multi-touch touchpad, 61 x 115 mm (2.40 x 4.53 inches)

#### Mechanical

### Dimensions (WxDxH)[1]

315.9 x 223.7 x 17.7 mm (12.44 x 8.81 x 0.7 inches)

### Weight<sup>[2]</sup>

Models	Weight
Models with black cover and 39.3Wh battery	Starting at 1.31 kg (2.89 lbs)
Models with grey cover and 39.3Wh battery	Starting at 1.36 kg (2.99 lbs)
Models with black cover and 52.5Wh battery	Starting at 1.38 kg (3.05 lbs)
Models with grey cover and 52.5Wh battery	Starting at 1.43 kg (3.15 lbs)

#### Case Color\*\*

- Black
- Grey

#### Case Material\*\*

- Models with black cover: PC + 20% CF (top), PC + 20% CF (bottom)
- Models with grey cover: aluminium (top), PC + 20% CF (bottom)

### Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

### CONNECTIVITY

### **Network**

### Ethernet\*\*

- Gigabit Ethernet, Intel® Ethernet Connection I219-LM (vPro® models), 1x RJ-45, supports Wake-on-LAN
- Gigabit Ethernet, Intel® Ethernet Connection I219-V (non-vPro® models), 1x RJ-45, supports Wake-on-LAN

### WLAN + Bluetooth®\*\*[1]

- Intel® Wi-Fi® 6E AX211, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.3[2]
- Intel® Wi-Fi® 7 BE200, 802.11be 2x2 Wi-Fi® + Bluetooth® 5.3 (Bluetooth® 5.4 hardware ready)[3]

### WWAN\*\*

- Wireless WAN upgradable to 4G (with antenna ready)
- Wireless WAN upgradable to 4G or 5G (with antenna ready)
- Quectel EM061K-GL, 4G LTE CAT6, M.2 Card, with embedded eSIM functionality
- Quectel EM160R-GL, 4G LTE CAT16, M.2 card, with embedded eSIM functionality
- Quectel RM520N-GL, 5G Sub-6 GHz, M.2 Card, with embedded eSIM functionality
- No support

#### SIM Card

No physical SIM card inbox



#### NFC<sup>[4]</sup>

- · Near Field Communication
- No support

#### Notes:

[1] Bluetooth® may operate at a lower version than hardware design depending on the factors such as operating system, driver, etc.

[2] Wi-Fi® 6E full features might be limited by country-level restrictions.

Wi-Fi® 6E is only enabled on Windows® 11 and operates as Wi-Fi® 6 with Windows® 10.

6GHz Wi-Fi® 6E operation is dependent on the support of the operating system, routers/APs/Gateways that support Wi-Fi® 6E, and the regional regulatory certifications & spectrum allocation.

Bluetooth® 5.3 operation requires Windows® 11. For more information please visit <u>General Bluetooth® Support Information on Microsoft®</u>.

[3] Wi-Fi® 7 is only enabled on Windows® 11 and operates as Wi-Fi® 6 with Windows® 10.

6GHz Wi-Fi® 7 operation is subject to the regulation rules in each country.

Bluetooth® 5.3 operation requires Windows® 11. For more information please visit <u>General Bluetooth® Support Information</u> on <u>Microsoft®</u>.

[4] NFC is NOT available for grey models.

#### Ports<sup>[1]</sup>

### **Standard Ports**

- 1x USB-A (USB 5Gbps / USB 3.2 Gen 1)
- 1x USB-A (USB 5Gbps / USB 3.2 Gen 1), Always On
- 2x USB-C® (Thunderbolt™ 4 / USB4® 40Gbps), with USB PD 3.0 and DisplayPort™ 2.1
- 1x HDMI® 2.1, up to 4K/60Hz
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Ethernet (RJ-45)

### Optional Ports\*\*\*

- 1x Smart card reader
- 1x Nano-SIM card slot (WWAN support models)

#### Notes:

[1] The transfer speed of the ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

## **Docking**

### **Docking**

Various docking solutions supported via Thunderbolt<sup>™</sup> / USB-C<sup>®</sup>.

For more compatible docking solutions, please visit Docking for ThinkPad® T14 Gen 5 (Intel®)

### **SECURITY & PRIVACY**

### **Security**

### **Security Chip**

Discrete TPM 2.0, TCG certified, FIPS 140-2 certified

### **Physical Locks**

Kensington® Nano Security Slot™, 2.5 x 6 mm

#### **Smart Card Reader**

- Smart card reader, supports ISO 7816 and EMV
- No smart card reader

#### Fingerprint Reader[1]

- · Touch style fingerprint reader integrated in power button, match-on-chip
- · No fingerprint reader

### **BIOS Security**

- NVMe® password
- Power-on password



- Supervisor password
- · System management password
- Certificate-based BIOS athentication
- FIDO (Fast Identity Online) authentication
- · Self-healing BIOS
- More BIOS security features, please visit BIOS Simulator[2]

#### Other Security

- Camera privacy shutter (camera models)
- (Optional) Ultrasonic Human Presence Detection
- (Optional) IR camera for Windows® Hello (facial recognition)
- Privacy Guard with Privacy Alert (models with ThinkPad® Privacy Guard display)

#### Notes:

[1] Fingerprint reader is standard on grey models and optional on black models.

[2] The BIOS simulator is just for reference. Default settings and some options may vary depending on the hardware, operating system and BIOS version.

### **MANAGEABILITY**

## **System Management**

### System Management\*\*

- Intel® vPro® Enterprise<sup>[1]</sup>
- Intel® vPro® Essentials
- Non-vPro®

#### Notes:

[1] Intel® vPro® offers a superset of DASH's defined capabilities.

### **SERVICE**

### Warranty

### Base Warranty\*\*

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 1-year limited onsite service
- 3-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) limited onsite service
- No base warranty

# **ACCESSORIES**

### **Bundled Accessories**

### **Bundled Accessories**\*\*\*[1]

- Lenovo® HDMI® to VGA Monitor Adapter
- Lenovo® USB-C® to DisplayPort™ Adapter
- Lenovo® USB-C® to Ethernet Adapter (1Gbps)
- Lenovo® USB-C® to VGA Adapter
- None

#### Notes:

[1] For more compatible accessory solutions, please visit Accessories for ThinkPad® T14 Gen 5 (Intel®).

# **OPERATING REQUIREMENTS**

## **Operating Environment**

Temperature[1]



- Operating: 5°C (41°F) to 35°C (95°F)
- Storage and transportation in original shipping package: -20°C (-4°F) to 60°C (140°F)
- Storage without package: 5°C (41°F) to 43°C (109°F)

#### **Relative Humidity**

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

#### Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

### **ENVIRONMENTAL**

## **Sustainability**

### Material<sup>[1]</sup>

30% PCC recycled plastic on black top cover

50% recycled aluminium on grey top cover

90% recycled magnesium on keyboard frame

45% PCC recycled plastic on bottom cover of WWAN models

30% PCC recycled plastic on bottom cover of non-WWAN models

90% PCC recycled plastic used in speaker enclosure

90% PCC recycled plastic used in the battery frame

85% PCC recycled plastic for backlit keycaps

70% PCC recycled plastic for non-backlit keycaps

90% PCC recycled plastic used in 65W and 65W slim adapters

Plastic free recycled standard packaging

Notes:

[1] PCC: Post Consumer Content, recycled materials from customers.

### CERTIFICATIONS

### 

### Green Certifications[2]

- ENERGY STAR® 8.0
- EPEAT™ Gold Registered<sup>[3]</sup>
- ErP Lot 6/26
- · RoHS compliant
- TCO Certified 10.0

#### Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <a href="https://compliance.lenovo.com">https://compliance.lenovo.com</a>.

[2] EPEAT™ registration and ENERGY STAR® certification are optional and only available on the models with preloaded OS. Please visit <u>epeat.net</u> and <u>energystar.gov</u> for more information.

[3] EPEAT™ is registered where applicable, please visit epeat.net for registration status by country.

#### Other Certifications

#### Mil-Spec Test

MIL-STD-810H military test passed

### **Other Certifications**

(Optional) Eyesafe® Certified 2.0

- Feature with \*\* means that only one option listed under the feature can be configured on selected models.

  Please refer to the model configuration for specific information.
- · Feature with \*\*\* means that one or more options listed under the feature can be configured on selected



models. Please refer to the model configuration for specific information.

- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
  responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
  WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
  OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
  disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
  you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.













