SPECIFICATIONS

	USW-Flex
Dimensions	122.5 x 107.1 x 28.0 mm (4.82 x 4.22 x 1.10")
Weight	230 g (8.11 oz)
Networking Interfaces	(5) 10/100/1000 Mbps RJ45 Ports
Management Interface	Ethernet In-Band
PoE Out (Ports 2-5)	802.3at (Pins 1, 2+; 3, 6-)
Max Power Consumption (Excluding PoE Output)	5W
Max PoE Wattage Per Port	25W
Total PoE Power Budget Powered by 802.3af Powered by 802.3at Powered by 802.3bt Powered by PoE Adapter (Enabled in Controller)	8W 20W 46W 46W
Voltage Range 802.3af 802.3at/bt	44 - 57V 50 - 57V
LEDs System RJ45 Data Ports	Status PoE; Link/Speed/Activity
ESD/EMP Protection	\pm 16kV Air, \pm 16kV Contact
Operating Temperature 46W PoE Output 25W PoE Output	-40 to 55° C (-40 to 131° F) -40 to 65° C (-40 to 149° F)
Operating Humidity	5 to 95% Noncondensing
Certifications	CE, FCC, IC

Power Method (Port 1)				
РоЕ Туре	802.3af/at (Pins 1, 2+; 3, 6-)	802.3bt (Pins 1, 2+; 3, 6- and 4, 5+; 7, 8-)	50V/60W PoE Adapter*	
Recommended PoE Source	USW-24-PoE (sold separately)	USW-Pro-24-PoE (sold separately)	PoE Injector, POE-50-60W-WH or POE-50-60W (sold separately)	

* To enable PoE output power, select **Power Source > PoE Injector** in UniFi Controller.





SPECIFICATIONS





	USW-Flex-Utility*
Dimensions (with Mount)	249 x 218 x 60 mm (9.80 x 8.58 x 2.36")
Weight (with Mount)	740 g (26.10 oz)

USW-Flex-Utility 60W PoE Adapter		
Dimensions	118.5 x 63 x 34.7 mm (4.66 x 2.48 x 1.36")	
Weight	206 g (7.27 oz)	
Output Voltage	54V, 1.11A	
Rated Voltage	100-240VAC	
Input Current	1.5A (Max.)	
Efficiency	> 86%	
Output Ripple	200mVpp	
Line Regulation	< 1%	
Load Regulation	< 3%	
4-Pair Powering	Pins 1, 2, 4, 5+ and Pins 3, 6, 7, 8-	
Operating Temperature	-20 to 60° C (-4 to 140° F)	
Storage Temperature	-30 to 70° C (-22 to 158° F)	
Operating Humidity	5 to 90%, Noncondensing	
Surge Immunity	4kV Difference and Common Mode	

* Accessory sold separately.

Specifications are subject to change. Ubiquiti products are sold with a limited warranty described at: ui.com/support/warranty

Specifications are subject to change. Upiquit products are sold with a limited warranty described at unconvsupport/warranty The limited warranty requires the use of arbitration to resolve disputes on an individual basis, and, where applicable, specify arbitration instead of jury trials or class actions. ©2019-2020 Ubiquiti Inc. All rights reserved. Ubiquiti, Ubiquiti Networks, the Ubiquiti Uogo, the Ubiquiti beam logo, UniFi, and UniFi Network are trademarks or registered trademarks of Ubiquiti Inc. in the United States and in other countries. Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc., registered in the U.S. and other countries. Android, Google, Google Play, the Google Play logo and other marks are trademarks of Google LLC. All other trademarks are the property of their respective owners.