

Boost productivity, reduce printing costs



Designed to meet the diverse needs of medium and large-sized companies, the ECOSYS MA4000fx is a flexible device that provides an all-in-one solution to increase productivity at a low running cost. With a very short wait time to first print, users enjoy fast, reliable, and efficient printing for less.



ECOSYS MA4000fx



A4 monochrome multifunctional

Up to 40 pages per minute

Duplex print, copy, scan, and fax

Specifications

GENERAL

KYOCERA ECOSYS Laser Monochrome Multifunctional

Operation panel: LCD 21 characters, 5 lines

Type: Desktop

Engine speed:

Up to 40 A4 pages per minute simplex (single-sided), Up to 20 A4 pages per minute duplex (both sides)

Resolution: 1200 x 1200 dpi (print),

600 x 600 dpi (scan/copy)

Recommended Print Volume: Average 2,000 pages per month

Maximum Print Volume: 80,000 pages per month

Maximum Life: 200,000 pages or 5 years

Recommended Scan Volume: Average 830 pages per month

Warm-up time: Approx. 19 seconds or less

(after switching on)

Time to first print: Approx. 6.4 seconds or less

Time to first copy: Approx. 7.4 seconds or less (DP),

Approx. 6.4 seconds or less (Platen)

Processor: ARM Cortex-A53, 1.0GHz

Memory: Standard 1GB

Standard interface: USB 2.0 (Hi-Speed), Network

(10BASE-T/100BASE-TX/1000BASE-T), USB host for

USB flash memory, slot for optional SD/SDHC card

Integrated accounting: 100 department codes

Dimensions (W x D x H):

Without packaging: 417 x 412 x 437 mm,

With packaging: 555 x 541 x 572 mm

Weight:

Without packaging: Approx. 19.5 kg (with bundled toner),

Approx. 19.0 kg (without bundled toner)

With packaging: 24 kg

Power source: AC 220 ~ 240 V, 50/60 Hz

Power consumption:

Printing/Copying: 574.4 W

Ready mode: 10.8 W

Sleep-mode: 0.4 W

Noise (sound pressure level: ISO 7779/ISO 9296):

Printing/Copying: 52 dB (A)

Quiet mode: 48 dB (A)

Stand-by: 29 dB (A)

Safety standards: TÜV/GS, CE

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard

PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions

Input capacity: Multi-purpose tray: 100 sheets, 60–220 g/m², A6, A5, A4, custom (70 x 148 – 216 x 356 mm). Standard universal paper cassette: 250 sheets, 60–163 g/m², A6, A5, A4, custom (105 x 148 – 216 x 356 mm). Max. input capacity with options: 850 sheets.

Duplex: Standard duplex unit, two-sided printing, 60–163 g/m², A5, A4, custom (140 x 210 – 216 x 356 mm).

Document Processor: max. 50 originals, duplex scan, 50–160 g/m², A6, A5, A4, custom (100 x 148 – 216 x 356 mm).

Output capacity: Max. 150 sheets (face-down) with paper full detection.

PRINT FUNCTIONS

Controller language: PRESCRIBE

Emulations: PCL 6 (Se, XL), KPDL3 (PostScript 3 compatible), Lineprinter, IBM Proprinter, Epson LQ-850, PDF Direct Print 1.7, 2.0, XPS/Open XPS Direct Print, TIFF Direct Print

Operating systems: All current Windows operating

ECOSYS stands for ECOlogy, ECOnomy and SYStem printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly. The modular design concept allows you to add workflow enhancing functions as required. Integrated system software provides long-term cross network compatibility. KYOCERA's long-life components cost you and the environment less.



KYOCERA Document Solutions (UK) Ltd,
Eldon Court, 75-77 London Road, Reading RG1 5BS
T: 0333 015 1855, F: 0118 931 1108
E: info@duk.kyocera.com



*KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

FAX FUNCTIONS

Compatibility: Super G3

Modern speed: Max. 33.6 kbps

Transmission speed: Max. 3 seconds (JBIG)

Scanning speed: 2 seconds or less

Address book: 300 entries

Scanning density:

Normal: 8 dot/mm x 3.85 line/mm (200 x 100 dpi)

Fine: 8 dot/mm x 7.7 line/mm (200 x 200 dpi)

Superfine: 8 dot/mm x 15.4 line/mm (200 x 400 dpi)

Ultrafine: 16 dot/mm x 15.4 line/mm (400 x 400 dpi)

Halftone: 256 grey scales

Maximum original size: A4/Legal

Compression method:JBIG, MMR, MR, MH

Memory reception: 256 sheets or more

Features: Network Fax, Memory Reception, Fax Polling,

Duplex Receive, Multiple Scan, Fax Forwarding, Fax Direct,

Scheduled transmission, Sub address, Fax dedicated paper source, Shared Fax Driver, text readability improvement

CONSUMABLES

Average continuous toner yield in accordance with

ISO/IEC 19752

TK-1270 Toner Kit: Microfine toner black for 10,000 pages A4. Capacity of starter toner is 3,600 pages A4.

OPTIONS

PF-1100 Paper feeder (max. 2 units): Max. 250 sheets, 60 – 163 g/m²; A6, A5, A4, custom (105 mm x 148 mm – 216mm x 356mm)

CB-1100-B Cabinet: Wooden desk with storage capacity and wheels, approx. 375 x 393 x 510 mm (WxDxH)

SECURITY

UG-33: ThinPrint support

UG-50: TPM (Trusted Platform Module),

additional protection of confidential data

USB IC Card Reader + Card Authentication Kit (B):

Support for various authentication keys available

WARRANTY

2-year warranty as standard. KYOCERA guarantees the drum and developer for 3 years or 100,000 pages (whichever occurs sooner), provided each device is used and cleaned in accordance with the service instructions.

KYOCERA LIFE

Up to 1-year on-site warranty extensions available for product and options

WHAT'S IN THE BOX:

Main unit, starter toner for 3,600 pages, Quick Guide, safety instructions, power supply cord, fax cable.

DVD with drivers, software and user manual not included. Computer with internet connection required to download drivers and software.

¹The device is not designed to achieve the specified volumes in continuous operation. The maximum volumes relate to the use of the print or scan unit and include their use for the printing, copying and scanning functions. Note: In this context, a copied page corresponds to a scanned and a printed page.

²Optional SD/SDHC memory card is required.

KYOCERA Document Solutions Partner

KDUKAUG2024MA4000fx/VER1.0



kyoceradocumentsolutions.co.uk