

OVERVIEW



1. Smart card reader *	5. 2x Thunderbolt 4
2. USB-A (USB 5Gbps)	6. HDMI
3. USB-A (USB 5Gbps), Always On	7. Headphone / microphone combo jack (3.5mm)
4. Kensington Nano Security Slot	8. Nano-SIM card slot *

Notes:

• Items with * are only available on selected models



PERFORMANCE

Processor

Processor Family

AMD Ryzen™ AI 7 PRO 300 Series Processor

Processor

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Processor Graphics	NPU
AMD Ryzen™ AI 7 PRO 360	8	16	2.0GHz	5.0GHz	8MB L2 / 16MB L3	AMD Radeon™ 880M	AMD Ryzen™ AI

Al (Artificial Intelligence)

AI PC Category

Copilot+ PC

Al Performance

Up to 72 overall TOPS

NPU

Integrated AMD Ryzen™ AI, up to 50 TOPS

Operating System

Operating System**

- Windows® 11 Pro
- Windows® 11 Home
- Fedora Linux[1]
- Ubuntu Linux^[2]
- Linux^[3]
- No preload operating system

Notes:

[1], [2], [3] Some features may not be supported on the system with Linux preload, including but not limited to Intel® RST RAID, MIPI computer vision camera, WWAN, Human Presence Detection, etc.

Graphics

Graphics

Graphics	Туре	Memory	TGP	Key Features
AMD Radeon™ 880M	Integrated	Shared	Share CPU TDP	DirectX® 12

Monitor Support

Monitor Support[1]

Supports up to 4 independent displays (native display and 3 external monitors via HDMI® and Thunderbolt™)

- HDMI® supports up to 4K@60Hz
- Thunderbolt[™] supports up to 8K@60Hz^[2]

Notes:

[1] Refresh rates >60hz also supported, however max resolution will be limited.

[2] 8K resolution support needs 2 display pipes. That is, simultaneous display number will "-1" when 8K resolution displayed.

Chipset

Chipset

AMD SoC (System on Chip) platform

Memory

Max Memory

• 32GB soldered memory, not upgradable

ThinkPad T14s Gen 6 (AMD)



• 64GB soldered memory, not upgradable

Memory Slots

Memory soldered to systemboard, no slots, dual-channel

Memory Type

LPDDR5x-7500

Storage

Storage Support[1]

One drive, up to 1TB M.2 2280 SSD

Storage Slot

One M.2 2280 PCIe® 4.0 x4 slot

Storage Type**

Disk Type	Interface	Offering	Security
M.2 2280 SSD	PCIe® NVMe®, PCIe® 4.0 x4 Performance	512GB / 1TB	Opal 2.0
M.2 2280 SSD	PCIe® NVMe®, PCIe® 4.0 x4	256GB	Opal 2.0

Notes:

[1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.

Removable Storage

Card Reader

No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC3287 codec

Speakers

Stereo speakers, 2W x2, Dolby Atmos®

Microphone

Dual-microphone array, 360° far-field, Dolby Voice®

Camera

5.0MP + IR discrete, with privacy shutter, fixed focus, temporal noise reduction

Battery

Battery^[1]

Integrated Li-Polymer 58Wh battery, supports Rapid Charge (charge up to 80% in 1hr)

Battery Life[2]

Configuration 1 (max battery life)

MobileMark $^{\! \circ}$ 25: up to 17.1 hr with 662 performance score @250nits

JEITA-BAT 3.0 (Video/Idle): up to 15.48 hr / 29.8 hr @200nits

Local video playback: up to 23.87 hr @150nits

Alternate configuration 2

MobileMark® 25: up to 15.01 hr with 629 performance score @250nits

JEITA-BAT 3.0 (Video/Idle): up to 13.56 hr / 22.4 hr @200nits

Local video playback: up to 22.3 hr @150nits

Notes:

[1] Rapid charge is only guaranteed when the computer is turned off or in standby mode or in hibernation mode. When the computer is powered on, the Charge Time will vary depending on system power consumption and AC adapter power.

[2] Configuration 1 (max battery life): WUXGA (non-touch), AMD Ryzen™ AI 7 PRO 360, 32GB LPDDR5x-7500, Win 11, 58Wh battery, best power efficiency power mode

Alternate configuration 2: WUXGA (touch), AMD Ryzen™ AI 7 PRO 360, 32GB LPDDR5x-7500, Win 11, 58Wh battery, best power efficiency power mode



All battery life claims are approximate maximum and based on results using MobileMark® 2018, MobileMark® 25, JEITA 2.0, continuous 1080p local video playback (using default Media Player in Fullscreen mode with 150nits brightness and default volume level), or Google Power Load Test (PLT) battery-life benchmark tests.

Actual battery life will vary depending on many factors such as product configuration, software, wireless functionality, power management settings, and screen brightness.

The maximum capacity of the battery will decrease with time, ambient temperature and use.

Refer to $\underline{\text{Microsoft}^{\text{\circ}} \text{ link}}$ for more information about the Windows $^{\text{$\circ$}} \text{ Performance power slider}.$

Power Adapter

Power Adapter**[1]

- 65W USB-C[®] (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C[®] (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® slim (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C[®] slim (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® slim GaN (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® slim GaN (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- No power adapter^[2]

Notes:

- [1] AC adapter offerings depend on the country.
- [2] No power adapter is for special bid only.

DESIGN

Display

Display**

Size	Resolution	Touch	Туре	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Refresh Rate	Viewing Angle (L/R/U/D)	Key Features
14"	WUXGA (1920x1200)	Multi- touch	IPS ^[1]	400nits	Anti- glare	16:10	600:1	45% NTSC	60Hz	85° / 85° / 85° / 85°	Eyesafe® Certified 2.0, 88% screen to body ratio, 3M™ DBEF5
14"	WUXGA (1920x1200)	None	IPS ^[2]	400nits	Anti- glare	16:10	800:1	100% sRGB	60Hz	85° / 85° / 85° / 85°	Low power, 88% screen to body ratio

Touchscreen

- On-cell multi-touch, supports 10-point touch
- Non-touch

Notes:

[1], [2] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

Input Device

Pen

No support

Keyboard

6-row, spill-resistant, multimedia Fn keys, Copilot key

Keyboard Backlight

LED backlight

UltraNav™

TrackPoint® pointing device, double-tap to open the TrackPoint® Quick Menu Glass-like Mylar® surface multi-touch touchpad, 61 x 115 mm (2.40 x 4.53 inches)

Mechanical



Dimensions (WxDxH)[1]

313.6 x 219.4 x 16.9 mm (12.35 x 8.64 x 0.67 inches)

Weight^[2]

Models	Weight
WUXGA Non-touch models	Starting at 1.30 kg (2.86 lbs)
WUXGA multi-touch models	Starting at 1.37 kg (3.02 lbs)

Case Color

Black

Case Material

Carbon fiber hybrid (top), aluminium (bottom)

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

Ethernet

No onboard Ethernet[1]

WLAN + Bluetooth®[2]

Qualcomm® Wi-Fi® 7 NCM825, 802.11be 2x2 Wi-Fi® + Bluetooth® 5.3 (Bluetooth® 5.4 hardware ready)[3]

WWAN**

- Wireless WAN upgradable to 5G (with antenna ready)[4]
- · Quectel RM520N-GL, 5G Sub-6 GHz, M.2 Card, with embedded eSIM functionality
- No support

SIM Card

No physical SIM card inbox

NFC

No support

Notes:

[1] Ethernet support via optional Lenovo® USB-C® to Ethernet Adapter.

[2] Bluetooth® may operate at a lower version than hardware design depending on the factors such as operating system, driver, etc.

[3] Wi-Fi® 7 is only enabled on Windows® 11 and operates as Wi-Fi® 6 with Windows® 10.

6GHz Wi-Fi® 7 operation is subject to the regulation rules in each country.

Bluetooth® 5.3 operation requires Windows® 11. For more information please visit <u>General Bluetooth® Support Information on Microsoft®</u>.

[4] Wireless WAN upgradable to 5G is only available in EMEA.

Ports^[1]

Standard Ports

- 1x USB-A (USB 5Gbps / USB 3.2 Gen 1)
- 1x USB-A (USB 5Gbps / USB 3.2 Gen 1), Always On
- 2x USB-C $^{\circ}$ (Thunderbolt $^{\text{\tiny TM}}$ 4 / USB4 $^{\circ}$ 40Gbps), with USB PD 3.0 and DisplayPort $^{\text{\tiny TM}}$ 2.1
- 1x HDMI® 2.1, up to 4K/60Hz
- 1x Headphone / microphone combo jack (3.5mm)

Optional Ports***

- 1x Smart card reader
- 1x Nano-SIM card slot (WWAN support models)



Notes:

[1] The transfer speed of the ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

Docking

Docking

Various docking solutions supported via Thunderbolt[™] / USB-C[®]. For more compatible docking solutions, please visit <u>Docking for ThinkPad[®] T14s Gen 6 (AMD)</u>

SECURITY & PRIVACY

Security

Security Chip

Discrete TPM 2.0 (TCG certified, FIPS 140-2 certified) and Microsoft® Pluton TPM 2.0, one enabled at one time

Physical Locks

Kensington® Nano Security Slot™, 2.5 x 6 mm

Smart Card Reader

- Smart card reader, supports ISO 7816 and EMV
- · No smart card reader

Fingerprint Reader

- Touch style fingerprint reader integrated in power button, match-on-chip
- · No fingerprint reader

BIOS Security

- NVMe® password
- · Power-on password
- Supervisor password
- System management password
- Certificate based BIOS authentication
- FIDO (Fast Identity Online) authentication
- Self-healing BIOS
- More BIOS security features, please visit <u>BIOS Simulator</u>

Other Security

- · Camera privacy shutter
- IR camera for Windows® Hello (facial recognition)
- Ultrasonic Human Presence Detection

MANAGEABILITY

System Management

System Management

Non-DASH

SERVICE

Warranty

Base Warranty**

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 1-year limited onsite service
- 3-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) limited onsite service
- No base warranty

ACCESSORIES



Bundled Accessories

Bundled Accessories***[1]

- Lenovo® HDMI® to VGA Monitor Adapter
- Lenovo® USB-C® to DisplayPort™ Adapter
- Lenovo® USB-C® to Ethernet Adapter (1Gbps)
- Lenovo® USB-C® to VGA Adapter
- None

Notes:

[1] For more compatible accessory solutions, please visit Accessories for ThinkPad® T14s Gen 6 (AMD).

OPERATING REQUIREMENTS

Operating Environment

Temperature[1]

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage and transportation in original shipping package: -20°C (-4°F) to 60°C (140°F)
- Storage without package: 5°C (41°F) to 43°C (109°F)

Relative Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

ENVIRONMENTAL

Sustainability

Material^[1]

30% recycled Carbon fiber on top cover

90% recycled magnesium on keyboard frame

55% recycled aluminum on bottom cover

85% PCC recycled plastic used in backlit keycaps

90% PCC recycled plastic used in speaker enclosure

90% recycled plastic used in the 58Wh battery frame

90% PCC recycled plastic used in standard 65W adapter

95% PCC recycled plastic used in cable / antenna holders

Plastic free packaging with FSC certified paper

Notes:

[1] PCC: Post Consumer Content, recycled materials from customers.

CERTIFICATIONS

Green Certifications^[2]

- ENERGY STAR® 8.0
- EPEAT™ Gold Registered^[3]
- ErP Lot 6/26
- RoHS compliant
- TCO Certified 10.0

Notes:

ThinkPad T14s Gen 6 (AMD)



[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit https://compliance.lenovo.com.

[2] EPEAT™ registration and ENERGY STAR® certification are optional and only available on the models with preloaded OS. Please visit <u>epeat.net</u> and <u>energystar.gov</u> for more information.

[3] EPEAT™ is registered where applicable, please visit epeat.net for registration status by country.

Other Certifications

Mil-Spec Test

MIL-STD-810H military test passed

Other Certifications

(Optional) Eyesafe® Certified 2.0

- Feature with ** means that only one option listed under the feature can be configured on selected models.

 Please refer to the model configuration for specific information.
- Feature with *** means that one or more options listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
 responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
 WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
 OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
 disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
 you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.







AMD









⊼DMA



