



Xerox® VersaLink® B625 Multifunction Printer is built on Xerox® ConnectKey® Technology. For more information, go to **ConnectKey.com**.

System Specification		
Speed ¹	Black-and-White: Up to 65/61 ppm Letter/A4 Duplex Print Speed: 39/37 ipm Letter/A4	
Monthly Duty Cycle ²	Up to 300,000 pages	
Recommended Average Monthly Print Volume	Up to 30,000 pages	
Processor/Memory/ Hard Drive	Quad Core 1.2GHz /4 GB system memory/ Optional : 500+GB HDD	
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 2.0 direct print, NFC; Optional: Wi-Fi®/Wi-Fi Direct® with Xerox® Dual Band WiFi® and Bluetooth® Kit (Bluetooth for iBeacon™)	
Controller Features	Unified Address Book, Remote Control Panel, Configuration Cloning, Fleet Orchestrator, Configuration Watchdog, Security Dashboard, Adaptive Learning	
Copy and Print		
Copy and Print Resolution	Copy: Up to 600 x 600 dpi; Print: Up to 1200 x 1200 dpi	
First-Print-Out Time (as fast as)	4.1 seconds black-and-white	
First-Copy-Out Time (as fast as) (from platen/ warmed-up state)	4.6 seconds black-and-white	
Page Description Language	Adobe® PostScript® 3™, Adobe® PDF, PCL® 5c/PCL® 6, Adobe(R) Embedded Print Engine (AEPE)	
Print Features	Print from USB, Print from Cloud Repositories (Dropbox, OneDrive, and Google Drive), Encrypted Secure Print, Xerox® Earth Smart, Job Identification, Booklet Layout, Store and Recall Driver Settings, Bi-directional Real-time Status, Scaling, Job Monitoring, Application Defaults, Two-sided Printing (as default), Hold All Jobs, Print Around, Print on Alternate Paper	
Mobile and Cloud Ready		
Universal Print Ready	Microsoft Universal Print is a cloud print service, available to Microsoft 365 subscribers. It removes the need for on-site print servers and leverages the built-drivers included in the Windows 10 and 11 PCs. You can enjoy the benefits of cloud hosting with a driverless setup for all Windows 10 and 11 clients. Utilize the Print Support App (PSA) by Xerox to gain access to the Xerox Print Properties user interface.	
Mobile Connectivity	Near Field Communication (NFC); Optional: Wi-Fi® Direct, Wi-Fi® (802.11 b/g/n/ac)AirPrint (iOS) including iBeacon ³ (Bluetooth) for AirPrint Discovery	
Mobile Printing	Mopria® Print, Apple® AirPrint®, Xerox® Print Service (Android), Xerox® @PrintByXerox App, Xerox® Easy Assist App; Optional: Xerox® Workplace App (iOS/Android), iBeacon³ (Bluetooth) for AirPrint Discovery	
Mobile Scanning	Mopria® Scan, Apple® AirPrint® Scan; Xerox® Easy Assist App; Optional: Xerox® Workplace App (iOS/Android), Scan to Microsoft OneDrive, Google Drive and DropBox	
Mobile Apps and Xerox App Gallery	Automate everyday processes with apps that translate, redact, eSign, personalize, print, convert, route, collaborate, and communicate. Visit xerox.com/WorkplaceApps to find apps by industry or workflow.	

Xerox® Workflow Central Platform	Optional: One-platform consistency for seamless productivity across computers, mobile devices and printers. With Workflow Central's ever-expanding suite of cloud-based workflows you can change documents into audio files for easy listening, convert PDF or image files to popular Microsoft formats for shareability with a wider audience, turn handwriting into legible, editable and shareable text, translate to/from over 40 different languages, and automatically redact Personal Identifiable Information using set words or phrases (xerox.com/en-us/office/software-solutions/workflow-central)	
Xerox® Workplace Suite and Xerox® Workplace Cloud	Optional: Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and a cloud based-version (Workplace Cloud) of this solution (xerox.com/en-us/office/print-management-solutions)	
Cloud Identity Provider (IdP) Integration	Use your desktop, laptop, or mobile login credentials to log in to your VersaLink MFPs with direct connections to popular cloud identity providers Okta, Ping Identity, and Microsoft® Azure	
Scan		
Standard Features	Destinations: Scan to USB/Email/Network SFTP, SMB, HTTP, HTTPS, FTP destinations; File Formats: PDF, PDF/A, JPEG, TIFF; Convenience Features: 1-Touch Apps, Optical Character Recognition (OCR), Password-protected PDF, Scan Preview, Scan to Folder, Scan to Home, Scan to Print, Searchable PDF, Single/Multi-Page PDF/TIFF, Touchless Workflow Accelerators, TWAIN Support, Unified Address Book	
Optional Features	Native Scan to Cloud Repositories (Dropbox, OneDrive, and Google Drive), Xerox® Scanning App for DocuShare®, other solutions available through various Xerox® Business Innovation Partners at xerox.com/Software-Solutions, Print from and Scan to Xerox® DocuShare® Go Content Management Platform	
Fax		
Standard Features	Fax Build Job, Network Server Fax Enablement	
Optional Features	Walk-up Fax one line, two-line available in select geographies, includes LAN Fax, Direct Fax, Fax Forward to Email, or SMB Share, Support for Fax over Voice over IP	
Security		
Standard Features	802.1x, Access Control, AES 256-bit, Audit Log, Automated threat response through Trellix DXL, Automatic Self-signed Certificate, Cisco® Identity Services Engine (ISE) Integration, Common Criteria Certification under collaborative Protection Profile for Hardcopy Devices (HCD cPP v1.0E) pending, Configuration Watchdog, Encrypted Secure Print, FIPS 140-3 (interim certification), EU Radio Equipment Directive (RED) Articles 3(3)(d) and (e) compliant, Firmware Verification, HTTPS, Immediate Image Overwrite for optional hard disks', IPsec, Job Level Encryption via HTTPS and Drivers, Local Authentication (Internal Database), LogRhythm SIEM integration, Microsoft Universal Print/IPP with Print Support Application (Secure Print and Secure Release), NFC Tap Authentication with Xerox® Easy Assist App, Network Authentication, Port/IP/Domain Filtering, Security Certificates utilizing ECDSA, Security Templates, Serverless Card Authentication, SFTP and Encrypted Email, SHA-256 Hash Message Authentication, SIEM integration (e.g Splunk, LogRhythm, Trellix ESM, and Microsoft Sentinel), Signed Email, SNMPv3, TLS1.1/1.2/1.3, Trellix Embedded Control Whitelisting, Trellix ePolicy Orchestrator®, Trusted Boot, Trusted Platform Module (TPM 2.0), User Access, User Permissions	
Optional Features	Trellix Integrity Control, Xerox® RFID Card Reader, Hard Disk (AES 256-bit, FIPS 140) with multi-pass Image Overwrite ⁷ , Xerox® Workplace Cloud/Suite Print Management and Content Security; WPA2™ and WPA3™ with Xerox® Dual Band WiFi® and Bluetooth® Kit (Bluetooth for iBeacon™), Xerox Workplace Cloud/Suite Print Management and Content Security, learn more at xerox.com/WorkplaceSolutions	
Print Management		
Standard Features	Xerox® Standard Accounting Tool (Copy, Print, Scan, Fax, Email), Network Accounting Enablement	
Optional Features	Xerox® Workplace Cloud/Suite, other network accounting solutions available through various Xerox® Business Innovation Partners. Xerox® Virtual Print Management Service; learn more at xerox.com/PrintManagement	
Optional Artificial Intelliger	nce Apps (Available via Xerox App Gallery)	
Optional Features	Xerox® Note Converter App utilizes the power of AI to make sense of handwriting, allowing you to quickly convert your notes into an MS Word document or a digital file. Easily edit, store, and share your notes with everyone in that important meeting you just left, saving you precious time. Learn more. Xerox® Summarizer App creates a summary of documents for viewing, printing, and emailing. Using artificial intelligence (AI), Xerox® Summarizer condenses dozens or even hundreds of pages by reducing the original scanned document to a percentage of the original or by creating a short and concise interpretation of the source text. Learn more.	
	Xerox® Auto-Redaction App takes advantage of cutting-edge AI technology in Google's Data Loss Prevention (DLP) software, which allows you to select preset Personally Identifiable Information (PII) or custom words and phrases and then automatically redact it. Learn more.	

Features and Accessories

Single-Pass Duplex Automatic Document

Feeder (DADF) saves time by simultaneously scanning both sides of two-sided documents with up to 150/144 ipm Letter/A4. High paper capacity drives productivity, especially for tasks that require large batches of scanned or copied documents.



The intuitive, tablet-like, 7-inch tiltable touch

screen allows you to personalize your experience to get more done in fewer taps. Gain access to an array of productivity boosting apps through the Xerox App Gallery. Try it out at xerox.com/SIM7.

The 100-Sheet Bypass Tray handles media sizes from 3 x 5 in to 8.5 x 14 in/76.2 x 127 mm to 216 x 356 mm

The 550-Sheet Tray handles media sizes from 3.9×7.5 in to 8.5×14 in/98.4 x 191 mm to 216 x 356 mm



OPTIONAL PAPER FEEDING

550-Sheet Tray

Add up to 3 additional 550-sheet trays for a total paper capacity of 2,300 pages.



2,100-Sheet Tray

Add an optional 2,100-sheet tray for even higher capacity. Can be combined with two optional 550-sheet trays. (Requires Caster Base)



OPTIONAL ACCESSORIES

Card Reader Kit

500+GB Hard Disk

Add to busy devices to enhance performance and increase capacity for storage, collation and image processing of large-size jobs, 1-Touch Apps, customer-installable fonts, and enable copy build job.



The Caster Base

Allows for easy moving of floor-standing configurations.



Wireless Network Adapter



Adjustable Stand



Printer Stand

XEROX® EASY ASSIST APP

With businesses moving to a more flexible work environment, workers need the right technology in place to keep productive and get back to what really matters. Xerox Easy Assist App allows you to easily and securely manage your device on the go right from your mobile phone, with mobile phone authentication using NFC tap, real-time monitoring of printer performance and instant access to self-support services - all without the need for any IT support. Learn more at xerox.com/EasyAssist.



Device Specification				
Control Panel Languages	US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan, Arabic, Croatian, Ukrainian			
Accessories				
Optional	500+GB HDD Convenience Stapler Scan To Cloud Enablement Kit Trellix Integrity Control Enablement Kit Unicode Font Kit ⁸ Wireless Network Adapter			
Electrical Requirements				
North America	Voltage: 110-127 VAC +/-10 % Frequency: 50/60Hz +/- 3 % , 11.6A			
Europe	Voltage: 220-240 VAC +/-10% Frequency: 50/60Hz +/- 3%, 5.3A			
Power Consumption				
Running (Average)	Simplex: 796W Duplex: 568W			
Standby Mode	31 watts			
Auto Off/Sleep Mode	1.7 watts (Default time to sleep mode = 1 minute)			
Warm-up (from Off)	As fast as 127 seconds			
Recovery from Sleep	As fast as 2.9 seconds			
Operating Environment				
Required Temperature Range	50 to 90°F/ 10 to 32.2°C			
Required Relative Humidity	8 to 80% RH			
Sound Power Levels	Operating: 7.2 B(A) or less Standby: 3.2 B(A) or less			
Sound Pressure Levels	Operating: 56 db(A) or less Standby: 14 db(A) or less			
Dimensions and Weight	Packaged	Unpackaged		
Base Configuration	Width: 27.6 in/701 mm Depth: 28.9 in/734 mm Height: 40.2 in/1021 mm Weight: 129 lb/3276 kg	Width: 22.0 in/558.8 mm Depth: 22.8 in/578.4 mm Height: 29.1 in/739.1 mm Weight: 97.2 lb/44.1 kg		
550-Sheet Tray	Width: 19.6 in/498 mm Depth: 23.5 in/598 mm Height: 7.7 in/196 mm Weight: 18.1 lb/8.2 kg	Width: 16.9 in/428 mm Depth: 20.1 in/510 mm Height: 4.3 in/110 mm Weight: 13.5 lb/6.2 kg		
2,100-Sheet Tray	Width: 21.4 in/543.49 mm Width: 16.9 in/428 mm Depth: 23.5 in/598 mm Depth: 20.1 in/510 mm Height: 18.9 in/479 mm Height: 13.8 in/350 mm Weight: 20.4 lb/6.8 kg Weight: 39 lb/17.7 kg			
Caster Base	Width: 34.0 in/864 mm Depth: 35.0 in/889 mm Height: 9.0 in/229 mm Weight: 63.1 lb/28.6 kg	Width: 20.5 in/521 mm Depth: 27.3 in/693 mm Height: 5.0 in/126 mm Weight: 17.4 lb/7.9 kg		
Printer Stand	Width: 20.7 in/525 mm Depth: 22.2 in/565 mm Height: 9.2 in/235 mm Weight: 37.7 lb/17.1 kg	Width: 18.2 in/463 mm Depth: 20 in/510 mm Height: 17.3 in/440 mm Weight: 32.7 lb/14.8 kg		
Adjustable Stand	Width: 27.2 in/690 mm Depth: 26.3 in/670 mm Height 9.1 in/232 mm Weight: 62.6 lb/28.4 kg	Width: 24.6 in/626 mm Depth: 23.5 in/597 mm Height: 20.5 in/521 mm Weight: 50.9 lb/23.1 kg		
System Certifications/Regula	atory Compliance			
Certifications		To view the latest list of certifications, go to xerox.com/OfficeCertifications		

Paper Handling	
Single-Pass Duplex Automat	tic Document Feeder (DADF)
Capacity ⁴	200 sheets
Speed (Up to)	Duplex: 150 ipm/144 ipm Letter/A4 (Color and Black-and-White) Simplex: 75 ppm/72 ppm Letter/A4 (Color and Black-and-White)
Paper Sizes	3.0 x 5.0 in to 8.5 x 14 in/76 x 127 mm to 216 x 355 mm
Weights	14 to 32 lb bond/52 to 120 gsm
Bypass Tray (Standard)	
Capacity ⁴	100 sheets
Sizes	Custom Sizes: 3 x 5 in to 8.5 x 14 in/76.2 x 127 mm to 216 x 356 mm
Weights	16 to 47 lb bond/60 to 176 gsm
Media Types	Bond Card Stock³ Custom Duplex Envelopes Hole Punched Labels Letterhead Lightweight Lightweight Card Stock Plain Preprinted Recycled
Trays 1 (Standard)	
Capacity ⁴	550 sheets
Sizes	Tray 1: Custom Sizes: 3.9 x 7.5 in to 8.5 x 14 in/98.4 x 191 mm to 216 x 356 mm
Weights	16 to 47 lb bond/60 to 176 gsm
Media Types	Bond Card Stock³ Custom Duplex Envelopes Hole Punched Labels Letterhead Lightweight Lightweight Card Stock Plain Preprinted Recycled

Paper Handling (continued)			
Additional Trays (Optional)	Additional Trays (Optional)		
Capacity ⁴	550-Sheet Tray: Add up to 3 additional 550-sheet trays 2,100-Sheet Tray: Add an optional 2,100-sheet tray. Can be combined with up to two optional 550-sheet trays. (Requires Caster Base)		
Sizes	3.9 x 7.5 in to 8.5 x 14 in/98 x 191 mm to 216 x 356 mm		
Weights	16 to 47 lb bond/60 to 176 gsm		
Media Types	Bond Card Stock ⁹ Custorn Duplex Envelopes Hole Punched Labels Letterhead Lightweight Lightweight Card Stock Plain Preprinted Recycled		
Total Capacity	Total Capacity		
Device Total Capacity ⁴	Base Model: 650 sheets 550-Sheet Tray: Add up to 3 additional 550-sheet trays for a total capacity of 2,300 sheets. 2,100-Sheet Tray: Add an optional 2,100-sheet tray for a total capacity of 2,750 sheets. Can be combined with up to two optional 550-sheet trays for a total capacity of 3,850 sheets. (Requires Caster Base) Paper Output: 550 sheets		

Сору	
First-Copy-Out Time (from platen/warmed up/ Black-and-White)	As fast as 4.6 seconds
Sides (input-output)	1-1, 1-2, 2-2, 2-1
Quantity	1 to 9,999
Resolution (max)	Up to 600 x 600 dpi
Reduction/Enlargement	Variable zoom from 25% to 400% in 1% increments
Concurrency	Program-ahead to allow job to be queued while initial job is processed (Copy, Print, Fax, and Scan)
Copy Features	Annotation and Bates™ stamping (with font size adjustment) Authentication for Services Auto Paper Select Auto Reduction & Enlargement (to fit selected paper size) Auto Tray Switching Automatic 2-sided/Duplex Booklet Creation Build Job (Enables page-level programming) Build Job is supported for all Copy (500+GB HDD³ is required) and ScanTo/Email/Workflow Scanning/Server Fax/Embedded Fax (500+GB HDD³ is not required) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Center option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Touchless Workflow Accelerators

Print		
Resolution (up to)	1200 x 1200 dpi	
Print Features	Application Defaults Banner Sheet Enable/Disable Booklet Layout Cover Selection Fit to New Paper Size Hold All Jobs Image Options (Resolution (Enhanced, High)) Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Layout/Watermark N-up (up to 16 pages per sheet) Paper Selection by Attribute Print From Cloud Repositories (Dropbox, OneDrive, and Google Drive) Sample Set Saved Job Secure Print with Timed Deletion Special Pages (exception page programming: covers, inserts, exception pages) Store and Recall Driver Settings Sustainability Features (Xerox® Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs) Two-sided Printing (as default) User Permissions	
Print from USB	Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, PS, PCL	
Operating Systems	Windows Server 2016 Windows Server 2019 Windows Server 2022 Windows 10 Windows 11 Mac OS 12.x, 13.x, 14.x Fedora® Core Ubuntu® iOS Android Note: For latest supported versions please visit our Drivers & Downloads page and specify your device at support.xerox.com	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD Microsoft Windows Networking over IP Support for Microsoft Universal Print Bonjour® AirPrint® Mopria® IPv6 Most protocols not in use can be disabled	
Font Capability	PCL: 93 scalable fonts, line printer, and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts	
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade, and manage Xerox® Devices and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls and simplifying print services management	
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy, and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos®, and others	
Unified Address Book for Fax, Email and Scan to		
Features	Services supported: Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favorites for quick access of all services supported	

Scan		
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs)	
Input Speed (up to)	Duplex: 150 ipm/144 ipm Letter/A4 (Color and Black-and-White) Simplex: 75 ppm/72 ppm Letter/A4 (Color and Black-and-White)	
Resolution	200 x 200 dpi to 600 x 600 dpi	
Bit Depth	1-bit (black-and-white), 8-bit (grayscale), 24-bit (color)	
Maximum Scan Area	8.5 x 14 in (215.9 x 355.6 mm), Legal	
Platen	Up to 8.5 x 14 in (216 x 356 mm) Document Feeder: Up to 8.5 x 14 in (216 x 356 mm)	
Scan Template Management	Support 250 scan templates Create Xerox® Embedded Web Server (EWS) scan templates and share via device cloning to other multifunction printers' confirmation sheet options	
Network Protocols	SFTP, FTP, SMB, HTTP, HTTPS	
File Compression	Color TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black-and-white TIFF (G3MH, G4 MMR compression – single or multiple pages) Searchable PDF/OCR and PDF/A-1b (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for black-and-white and within MRC)) Linearized PDF/PDF/A	
Document Management Fields (Metadata)	Features only available in Network Scan to File Templates: 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value, and other configurations Customized fields viewed on user interface for variable data input Scan To with Metadata; Embedded in scan files using XMP formats Works with expert systems workflow	
Scan Features	Auto Background and Shadow Suppression Bound Originals Compression Quality/File Size Control Edge Erase Mixed Size Originals Scan Build Job Original Type (Photo and Text, Photo, Text, Map, Newspaper/Magazine) Reduction/Enlargement Single Touch Scan buttons (up to 10) Size for Size (for mixed size originals) Touchless Workflow Accelerators TWAIN Support/WIA 2.0 Support	
Scan to Email (Standard)		
Scan Features	Auto send to self Create scan files based on image count Email signatures (6 lines each of 128 character max), email message body (user configurable), email Embedded Web Server confirmation sheet options Email signing (requires Smart Card option) Scan to Email S/MIME Encryption Touchless Workflow Accelerators	
Directory Access	Address list via LDAP (Windows Active Directory, Exchange, Notes, Domino), Device Address Book	
Scan To		
Standard Features	Create scan files based on image count Scan to Email Scan to Home Scan to Mailbox Scan to Network (using Secure FTP/HTTP/HTTPS) Scan to Network Folder (using Secure FTP/HTTP/HTTPS) Scan to PC/Server Client (SMB or FTP) Scan to Print Scan to USB Touchless Workflow Accelerators	
Optional Features	Native Scan to Cloud Repositories (Dropbox, OneDrive, and Google Drive)	
Xerox ConnectKey Scan Apps		
Scanning Apps and Xerox App Gallery	Scan to: Dropbox, Google Drive, Microsoft OneDrive, Microsoft Office 365, Box, Xerox® Workplace App (iOS/Android) See the full list of apps available in the Xerox App Gallery: xerox.com/AppGallery	

Security

Features

- Audit Log
- Cisco® Identity Services Engine (ISE) compatible
- Configuration Watchdog (Monitors and remediates 75 security settings in the following areas):
 - 802 1x
 - Admin Password Reset
 - Audit Log
 - Automatic Software Upgrade
 - Fmail Alerts
 - FIPS 140-3 (interim certification)
 - Hold All Jobs
 - Immediate Job Overwrite⁷
 - Installation Policies
 - PII Login Name
 - PostScript Passwords
 - Remote Services Enablement
 - Remote Start (TWAIN)
 - Reprint Saved Jobs
 - Scan to Mailbox (Internal storage)
 - Scheduled Disk Overwrite⁷
 - Secure Passcode Length
 - Secure Print Device Policies
 - SIEM
 - SNMP
 - System Timeout
 - Trellix Embedded Control
 - USB (Print from USB)
 - USB (Scan to USB)
 - USB Port Management
 - User Data Encryption
- Disable FTP
- Expanded Authentication
 - Digitally signed PDF (when using Smart Card authentication)
 - Encrypted and authentication to SMTP server for Scan to Email
 - Encrypted/Password Protected PDF (when using Email and Network Scan Templates only)
 - $\ \ FIPS\ 140-3\ (interim\ certification),\ 256\ bit\ Hard\ Disk\ Encryption^7,\ TLS\ 1.1/1.2/1.3,\ IPPS,\ HTTPS,\ SFTP,\ SNMPv3$
 - Immediate Image Overwrite/Securely delete jobs using approved algorithms⁷
 - NFC tap authentication with Xerox® Easy Assist App
 - Local Authentication (internal database)
 - Network authentication to access device and/or device services via Kerberos (UNIX/Windows Server 2008), SMB (Windows Server 2008, Windows Server 2012), NDS, LDAP authentication
 - Smart Card authentication 144k CAC/PIV Card Support (2048 bit certificate key)/.NET
 - Secure Data
 - USB PIV Security tokens such as Yubikey (requires the installation of the USB Token Hub kit)
 - Secure Print (up to 10 digit PIN or Network Authentication)
- Expanded Authorization
 - Authorization per user per service
 - SA access based on network credentials
 - Secure Network Access
 - User Permissions required to access Print and Print Features (e.g., time restrictions) reflects in the print driver
- Full System Common Criteria Certification under collaborative Protection Profile for Hardcopy Devices (HCD cPP v1.0E) pending will be made available in a future firmware release
- Hide Print Job Names
- IP Filter, IPsec, IPv6, TLS V1.0, V1.2, V1.3, SNMP V1/V2/V3, HTTPs, 802.1X, SFTP
- Secure Print (up to 10 digit PIN or Network Authentication)
- Security Dashboard
- SIEM support using Common Event Format (CEF), such as Trellix ESM, LogRhytm, Splunk, and any cloud-based SIEM that uses an on-premises collector-forwarder that utilizes the syslog format, for example Microsoft® Sentinel
- Security Templates
- Splunk SIEM integration
- Trellix Embedded Control (whitelisting), Trellix Integrity Control (optional)
- Trusted Platform Module 2.0
- USB port disablement

Fax		
Walk-up Fax Features		
Compatibility	ITU (CCITT) Group 3	
Speed/Modems	Single V.34 modem. V.34 33600 – 2400 BPS. Less than 4 seconds per page transmission time	
Compression/Speed	MH/G3, MR/G3, MMR/SG3, JBIG/SG3	
Resolution	Walkup Send: BW Resolution Standard 200 x 100 dpi (Send) 200 x 100 dpi, 204 x 98 dpi (Receive) Fine 200 x 200 dpi (Send) 200 x 200 dpi, 204 x 196 dpi (Receive) SuperFine 300 x 300 dpi (Send) 300 x 300 dpi, 204 x 391 dpi (Receive) UltraFine 600 x 600 dpi (Send) 600 x 600 dpi, 400 x 400 dpi, 408 x 391 dpi (Receive) Color Resolution Fine 200 x 200 dpi (Send) 200 x 200 dpi (Receive) SuperFine 300 x 300 dpi (Send) 300 x 300 dpi, 400 x 400 dpi (Receive) Receive: Accepts all sizes	
Fax Send Features	Automatic Cover Sheets Auto Fax Transmission Reduction Automatic Memory Resend Batch Send (up to memory capacity) Delay Start, Build Job, Favorites Device Address Book (up to 5,000 contacts) LAN Fax (fax from print driver) Page-by-page Job Status at the Machine PSTN Fax Support for Fax over Voice over IP Touchless Workflow Accelerators	
Fax Receive Features	Auto Answer Delay One- or Two-sided Printing Output Tray Selection Receive Print Mode – Manual (size, margin, stock, header)/Auto Receive Timestamp Secure Receive Support for Fax over Voice over IP Up to 200 Password-protected Mailboxes	
Fax Forward	Forward to Email or SMB Location Fax Forward on Receive Only	
Fax Reports	Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On Demand Overwrite ⁷ Report, Mailbox Report, Broadcast Report	
Directory Access	Utilizes the Unified Address Book Group fax available	
Auto Redial	Up to 14 attempts (per country requirements) 1 to 25 minute intervals	
Auto Resend	Up to 5 attempts	

Device Management		
Administrative Protocols	DHCP, BOOTP, SNMP, SLPv2, HTTP, HTTPS, AutoIP (Self Assigned Address), TLS, NTP, DNS, SMB, SMTP/POP3, WSD, LDAP, Multicast DNS, Bonjour, syslog (for SIEM)	
Xerox Easy Assist App	Xerox Easy Assist App allows you to easily and securely manage your device on the go right from your mobile phone, with real-time monitoring of printer performance and instant access to self-support services – all without the need for any IT support.	
Management Support	NMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP AIB access (IETF-MIBII RFC 1213) lost Resources MIB RFC 2790, Printer MIB RFC 3805, PWG-Imaging-System-Power MIB, Fleet Orchestrator, Configuration Watchdog, Security Dashboard, Alerox Easy Assist	
Xerox® CentreWare® Web Software	 A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running on Windows, UNIX, or any other operating system: Works with any SNMP-managed printer from any manufacturer Remote configuration of SNMP v3 Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management Auto-detect Xerox® CentreWare® Web Software server and download configurations files for touchless remote install 	
Xerox® Device Manager	Optional: Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor, and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: Device monitoring and troubleshooting Support for Xerox Printer Security Audit Service and Advanced Security Services Remote configuration of SNMP v3 Extensive reporting and discovery of new devices Usage collection, chargeback, and billing capabilities Auto-detect Xerox® Device Manager server and download configurations files for touchless remote install	
Xerox® Workplace Cloud	Optional: Remote management to set and audit device configuration data with Xerox® Workplace Cloud, eliminating the need for an on-site server	
Xerox® Workplace Cloud Fleet Management	Optional: Xerox® Workplace Cloud Fleet Manager collects and manages the data that drives fact-based decisions for your device management environment, from SMB to Enterprise. It is a cloud-based tool with minimal to no on-site hosting required, to configure, manage, monitor, and report on networked devices – regardless of vendor – αcross your organization. Xerox® Workplace Cloud Fleet Management provides: • Device monitoring and troubleshooting • Support for Xerox Printer Security Audit Service and Advanced Security Services • Remote configuration of SNMP v3 • Extensive reporting and discovery of new devices • Usage collection, chargeback, and billing capabilities • Part of the integrated Xerox Workplace platform for Fleet Management and Print Management	
Accessibility	 Embedded Web Server conforms to Web Content Guidelines (WCAG) Private listening support via USB headphones/USB audio adapter Speech output Touchscreen tilt and user interface inversion Touchscreen navigation with keyboard 	
Fleet Orchestrator	Fleet Orchestrator feature offers the ability to create a group of devices that share information with each other via a secure peer-to-peer connection. The following data can be shared: Software update files, clone files, and 1-Touch App files. Auto-assembly feature allows a new VersaLink® to automatically set itself up on the network to be automatically configured	
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® Printers and Multifunction Printers. As an SAP customer, you benefit from having SAP-certified Xerox® Device types available right from SAP'sonline delivery model. SAP-certified device types for Xerox® Printers and Multifunction Printers are available to download office.xerox.com/Software-Solutions	
Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. Information available at office.xerox.com/Software-Solutions	
Xerox® Embedded Web Serve	er – Integrated Device Web Pages Provided by the Device	
Device Status	Web server embedded in Network Controller: Tray status/contents Consumables status Alerts Remote Control Panel	
Job Submission	Print-ready files: PS, PCL, TIFF, PDF, JPG, TXT, PRN Output feature selection (2-sided, collate, orientation, output destination) Delivery options (Immediate, sample set, delay, secure, save job for reprint)	
Device Administration	Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator, Security Dashboard, Security Templates	
Browsers	Brave Browser Chrome Microsoft Edge Mozilla Firefox Opera Safari	
Support	Install print/scan drivers and online support available via support.xerox.com	
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic, Ukrainian, Croatian	

Remote Services			
Xerox® Automatic Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time		
Xerox® Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® Devices based on actual usage, eliminating the need to manually manage supplies inventory		
Xerox® Workplace Cloud Direct	Embedded device agent technology allows your printer to connect directly with Xerox Workplace Cloud for a zero network footprint offering a 'true' cloud-only Print Management and Mobile solution		
Accounting			
Xerox® Standard Accounting	(Standard)		
Tracking	Copy, Print, Fax, Scan and Email usage		
Accounting	Up to 2,495 User Accounts (User ID) Up to 500 General Accounts (Client) Up to 498 Group Accounts (Department)		
Features	 Administrator can manage the feature via the Web User Interface or device control panel in tools Administrator has the ability to import or export User Accounts, Group Accounts, General Accounts, and User Limits via an industry standard CSV file 		
Accounting Options – Netwo	rk Accounting (Allows central server to manage all accounting)		
	 Enhanced network accounting with up-to-the-minute data on how the system is being used Comprehensive management and enterprise-scale tracking and reporting of device usage of copy, print, scan, and server fax Numerous solutions are available through Xerox Alliance Partners. For details, visit xerox.com Security enhancements with the addition of HTTPS protocol support Device requests account authentication from third-party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third-party Networking Account Interface with third-party accounting terminal for accounting user interface 		
Installation Considerations			
Clear area around the device is necessary for access and ventilation. The table to the right shows the area needed on each side for correct installation.	Recessary for deventilation. to the right rarea needed de for		
What's In The Box	What's In The Box		
All items contαined in the box:	Xerox® VersaLink® B625 Multifunction Printer AC Power Cord Installation Guide Product Information Flyer Product Safety Sheet Software Update Flyer Software and Documentation CD Black Print Cartridge: 10,000 page capacity ⁵		

Supplies and Accessories	North America and Europe#	All other regions
Genuine Xerox Black Standard Capacity Toner Cartridge, Xerox® VersaLink® B625 Multifunction Printer (10,000 Pages) ⁵	006R04668	N/A
Genuine Xerox Black High-Capacity Toner Cartridge, Xerox® VersaLink® B625 Multifunction Printer (25,000 Pages) ⁵	006R04669**	006R04672
Genuine Xerox Black Extra High-Capacity Toner Cartridge, Xerox® VersaLink® B625 Multifunction Printer (42,000 Pages) ⁵	006R04670	006R04673
Genuine Xerox Black Imaging Kit, Xerox® VersaLink® B625 Multifunction Printer (150,000 Pages) ⁶	013R00699	013R00699
Optional Accessories		
550-Sheet Tray	097N02445	
2,100-Sheet Tray	097N02446	
500+GB Hard Disk	097N02443	
Wireless Network Adapter	097N02444	
Printer Stand 097S05244		
Caster Base 097N02447		
Adjustable Stand	497N07994	

[#] North America (NA): U.S., Canada

Europe (XE): U.K., France, Germany, Spain, Italy, Netherlands, Belgium, Norway, Sweden, Finland, Denmark, Iceland, Luxembourg, Austria, Switzerland, Portugal, Ireland Andorra, Azores, Corsica, Greenland, Iceland, Lichtenstein, Luxembourg, Madeira, San Marino

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling program. Visit xerox.com/About-Xerox/Recycling.

For more information, visit us at xerox.com/Office.



^{**} Available in North America only

Declared in accordance with ISO/IEC 24734.
 Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.
 Wireless Network Adapter is required for iBeacon.
 Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

⁵ Average standard pages. Declared in accordance with ISO/IEC 19752. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, media orientation, run mode, application types, monthly print volumes, and image quality set-points.

⁶ Average drum yield is based on a run length of 5 pages of 8.5 x 11 in/A4 LEF. ⁷ Requires 500+GB Hard Disk.

Not available in all geographies.
 Weight: 16 to 47 lb bond/60 to 203 gsm.