

PATH TO THE FUTURE

Introducing the MSI MAG 274F esports gaming monitor. This cutting-edge monitor features a 27-inch FHD display with a lightning-fast 200Hz refresh rate and a rapid 0.5ms (GtG, Min.) response time. With the MAG 274F, you will have the competitive advantage needed to outperform and defeat your opponents in gaming battles.



Picture and logos

SELLING POINTS

- Panel Rapid IPS – oferuje szybki, 0,5-milisekundowy czas reakcji (GtG, min.) matrycy, optymalizuje kolory i jasność ekranu.
- Częstotliwość odświeżania 200 Hz – Reaguj znacznie szybciej dzięki dużo bardziej płynnemu wyświetlaniu klatek obrazu na ekranie monitora.
- 0,5-milisekundowy czas reakcji (GtG, min.) matrycy – ciesz się płynnym generowaniem klatek obrazu i brakiem efektu rozmycia nawet podczas wyświetlania najbardziej dynamicznych, kontrastowych scen.
- AI Vision – nowa technologia AI Vision może nie tylko ujawnić szczegóły ukrywające się w ciemnych obszarach ekranu, ale także zwiększyć ogólną jasność i nasycenie kolorów.
- Technologia Less Blue Light – Zastosuj software’owe rozwiązanie, które zmniejszy emisję niebiesko-fioletowego światła w obszarze niebieskiego widma.



1. 5-way Joystick Navigator
2. HDMI™ 2.0b (FHD@200Hz)
3. Display Port 1.2a (HBR2)
4. Headphone out
5. DC-in
6. Kensington Lock



MONITORY
MAG 274F
MAG 274F

SPECIFICATION

Model	Part No	9S6-3CE41H-001
	Color	ID1/Black-Black
Display	Screen Size	27" (68.58 cm)
	Active Display Area (mm)	597.888(H) x 336.312(V)
	Curvature	Flat
	Panel Type	Rapid IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.3114(H)x0.3114(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~200Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	TBD
	Refresh Rate	200HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	0.5ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	N/A
	NTSC (CIE1931 area percentage/overlap)	N/A
	sRGB (CIE1976 area percentage/overlap)	N/A
	sRGB (CIE1931 area percentage/overlap)	N/A
	Adobe RGB (CIE1976 area percentage/overlap)	N/A
	Adobe RGB (CIE1931 area percentage/overlap)	N/A
	DCI-P3 (CIE1976 area percentage/overlap)	N/A
	DCI-P3 (CIE1931 area percentage/overlap)	N/A
	Rec.709 (CIE1976 area percentage/overlap)	N/A
	Rec.709 (CIE1931 area percentage/overlap)	N/A
	Rec.2020 (CIE1976 area percentage/overlap)	N/A
	Rec.2020 (CIE1931 area percentage/overlap)	N/A
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
I/O Ports	Headphone-out	1
	Lock type	Kensington Lock
	HDMI	1
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.3
Warranty	Warranty	36M
Power	Power Type	TBD
	Power Input	N/A
	On-mode Power Consumption (KWh/1000h)	N/A
	Annual Energy Consumption (KWh)	N/A
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0..3
	Energy Efficiency Rating	N/A
	Power Cord Type	C13



MONITORY
MAG 274F
MAG 274F

Accessories	DisplayPort Cable	N/A
	HDMI Cable	1
	DVI Cable	N/A
	USB Type A to Type B Cable	N/A
	USB Type C to Type A Cable	N/A
	USB Type C to Type C Cable	N/A
	Thunderbolt Cable	N/A
	VGA Cable	N/A
	3.5mm audio Cable	N/A
	3.5mm combo audio Cable	N/A
	3.5mm Mic Cable	N/A
	Power Cord	N/A
	AC Adaptor	N/A
	Quick Guide	N/A
	Warranty Card	N/A
	Mouse Bungee Unit	N/A
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	N/A
	Product Dimension without Stand (WxDxH) (mm)	N/A
	Stand Dimension (WxDxH) (mm)	N/A
	Weight (Net kg)	N/A
	Weight Without Stand (kg)	N/A
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	N/A
	Outer Carton Dimension (WxDxH) (cm)	N/A
	Weight (Gross kg)	N/A
Barcode Info	EAN	4711377277105