



APC Smart-UPS C, Line Interactive, 2000VA, Rackmount 2U, 230V, 6x IEC C13 outlets, USB and Serial communication, AVR, Graphic LCD

SMC2000I-2U

#### **Overview**

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead time	Usually Ships within 2 Weeks

#### Main

Product or component type Uninterruptible power supply (UPS)

## **Batteries & Runtime**

Run Time	View Runtime Graph ☐
Battery type	Lead-acid battery
Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Battery life	35 year(s)
Replacement battery	APCRBC159 ☐
Battery charger power	144 W rated

## **General**

Provided equipment	CD with software Documentation CD Installation guide Rack mounting brackets USB cable
Number of power module	0
Number of power module filled slots	0
Number of power module free slots	0
product web sub-family	Entry level
Redundant	No

## **Physical**

Number of rack unit 21

Number of cables	1	
Colour	Black	
Height	8.9 cm	
Width	48 cm	
Depth	47 cm	
Net weight	26.2 kg	
Mounting location	Front	
Mounting preference	Lower	
Mounting mode	Rack-mounted	
Two post mountable	1	

## Input

Main Input Voltage	230 V
Input Connection Type	IEC 320 C20
Input voltage limits	180287 V
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

# Output

Main Output Voltage	230 V
Rated power in W	1300 W
rated power in VA	2000 VA
output connection type	6 IEC 320 C13 2 IEC Jumpers
Harmonic distortion	Less than 5 %
Maximum configurable power in VA	2000 VA
Maximum configurable power in W	1300 W
Transfer time	8 ms typical : 10 ms maximum
UPS type	Line interactive
Wave type	Sine wave
Output frequency	50 Hz sync to mains

# Conformance Product certifications

Product certifications	C-Tick			
	CE			
	EAC			
	GOST			
	IRAM SABS VDE			
				UK PSTI
				Marking
	Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006		
	EN/IEC 62040-2:2018			
	EIV/IEC 02040-2.2018			

## **Environmental**

Acoustic level	42 dBA
Heat dissipation	81 Btu/h
Operating altitude	010000 ft
Ambient air temperature for operation	040 °C
Ambient air temperature for storage	-1545 °C
Storage altitude	0.000000000015240.0000000000 m
Relative humidity	095 %
Storage Relative Humidity	095 %

# **Communications & Management**

control panel	Multifunction LCD status and control console
Free slots	0
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

# **Surge Protection and Filtering**

Surge energy rate	300 J	
Noise suppression	Full time multi-pole noise filtering: 0.3% IEEE surge let-through: zero clamping response time: meets UL 1449	

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25 cm
Package 1 Width	60 cm
Package 1 Length	59 cm
Package 1 Weight	30.16 kg

# **Contractual warranty**

Warrantv	2 years renair or replace	



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	3225
Environmental Disclosure	Product Environmental Profile

## **Use Better**

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	0637234b-27c7-4e32-ae29-543dd4803a99
REACh Regulation	REACh Declaration
<sup>☼</sup> Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

## **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

# **Product datasheet**

## SMC2000I-2U

Image of product / Alternate images

**Alternative** 



